

# 屋内照明器具特性

|         |                             |          |
|---------|-----------------------------|----------|
| 品番 (品名) | XND1061WN                   |          |
| 光源      | LED5000_85_1065 ×1          | 1065.0lm |
| 管理番号    | K0158971(0)DB1              |          |
| BZ分類    | BZ2/0.9/BZ1/4.5/BZ2/6.0/BZ1 |          |

|        |                 |         |                 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |  |     |
|--------|-----------------|---------|-----------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|--|-----|
| 器具効率   | 100%            | 天井      | 80%             |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |     | 0% |    |    |  |     |
|        | 上方光束<br>0%      |         | 反射率             | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10 | 0% |    |  |     |
| 下方光束   | 100%            | 床       |                 | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |     |    | 0% |    |  |     |
| 室指数    |                 |         | 照明率 (X0.01)     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |  | ZCM |
| 保守率    | 良               | 0.81    | 0.6             | 70  | 61  | 55  | 51  | 69  | 60  | 55  | 51  | 67  | 59  | 54  | 51  | 65  | 59  | 54  | 50 | 49 |    |  |     |
|        | 中               | 0.77    | 0.8             | 80  | 72  | 66  | 62  | 79  | 71  | 66  | 62  | 77  | 70  | 66  | 62  | 75  | 69  | 65  | 62 | 60 |    |  |     |
|        | 否               | 0.68    | 1.0             | 86  | 79  | 74  | 70  | 85  | 78  | 73  | 70  | 83  | 77  | 73  | 69  | 81  | 76  | 72  | 69 | 67 |    |  |     |
|        |                 |         | 1.25            | 91  | 85  | 80  | 76  | 90  | 84  | 80  | 76  | 87  | 83  | 79  | 76  | 85  | 81  | 78  | 75 | 73 |    |  |     |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5             | 94  | 88  | 84  | 81  | 93  | 88  | 84  | 80  | 90  | 86  | 83  | 80  | 88  | 85  | 82  | 79 | 77 |    |  |     |
|        | 等価発光面積          |         | cm <sup>2</sup> | 2.0 | 98  | 93  | 90  | 87  | 96  | 92  | 89  | 86  | 94  | 91  | 88  | 86  | 92  | 89  | 87 | 85 | 83 |  |     |
| 取付高さ   | 器具間隔最大限         |         | 2.5             | 100 | 96  | 93  | 91  | 99  | 95  | 93  | 90  | 96  | 94  | 91  | 89  | 94  | 92  | 90  | 88 | 86 |    |  |     |
|        | 横方向 (A)         | 縦方向 (B) | 3.0             | 101 | 98  | 96  | 93  | 100 | 97  | 95  | 93  | 98  | 95  | 93  | 92  | 96  | 94  | 92  | 90 | 88 |    |  |     |
| Hm     | 1.29Hm          | 1.29Hm  | 4.0             | 103 | 101 | 99  | 97  | 102 | 100 | 98  | 96  | 100 | 98  | 96  | 95  | 98  | 96  | 95  | 93 | 91 |    |  |     |
|        |                 |         | 5.0             | 104 | 102 | 101 | 99  | 103 | 101 | 100 | 98  | 101 | 99  | 98  | 97  | 99  | 97  | 96  | 95 | 93 |    |  |     |
|        |                 |         | 7.0             | 106 | 104 | 103 | 101 | 104 | 103 | 102 | 101 | 102 | 101 | 100 | 99  | 100 | 99  | 98  | 97 | 95 |    |  |     |
|        |                 |         | 10.0            | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 103 | 103 | 102 | 101 | 101 | 101 | 100 | 100 | 99 | 96 |    |  |     |

