

屋内照明器具特性	
品番 (品名)	LGB57518K
光源	LDA7L-D-G/S/Z6 x5 810.0 lm
管理番号	K0165408 (0) DB 1
BZ分類	BZ6

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		25 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		63 %																								
保守率		良 中 否	0.67	0.6	44	34	27	22	42	32	26	21	37	29	24	20	33	27	22	18	15					
			0.63	0.8	52	42	35	30	49	40	33	29	44	36	31	27	39	33	28	25	21					
			0.56	1.0	58	48	41	35	54	46	39	34	49	41	36	32	43	37	33	29	25					
				1.25	62	53	47	41	59	51	45	40	53	46	41	37	47	42	38	34	29					
下方投影面積		cm ²		1.5	66	58	51	46	63	55	49	44	56	50	45	41	50	45	41	38	32					
等価発光面積			cm ²	2.0	71	64	58	53	67	61	55	51	60	55	51	47	54	50	46	43	37					
取付 高さ	器具間隔最大限			2.5	74	68	62	58	70	65	60	56	63	59	55	51	57	53	50	47	40					
	横方向 (A)		縦方向 (B)	3.0	76	71	66	62	72	67	63	59	65	61	58	55	59	56	53	50	43					
H m	1.14 H m	1.14 H m		4.0	79	74	70	67	75	71	68	64	68	65	62	59	62	59	56	54	46					
				5.0	81	77	73	70	77	74	70	68	70	67	65	62	63	61	59	57	49					
				7.0	83	80	77	75	79	77	74	72	72	70	68	66	65	64	62	60	52					
				10.0	85	82	80	78	81	79	77	75	74	72	71	69	67	66	65	63	55					

