

屋内照明器具特性	
品番 (品名)	LGB57690K
光源	LDA7L-D-G/S/Z6 ×6 810.0 lm
管理番号	K0164950 (0) DB 1
BZ分類	BZ6

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		31 %	室指数	照明率 (X0.01)																	Z	C	M
下方光束		57 %																					
保守率		良 中 否	0.67	0.6	44	34	27	22	41	32	26	21	36	29	23	20	32	26	21	18	14		
			0.63	0.8	52	42	35	29	49	39	33	28	43	35	30	26	37	31	27	23	19		
			0.56	1.0	57	47	40	35	53	45	38	33	47	40	35	30	41	35	31	28	22		
				1.25	62	53	46	41	58	50	44	39	51	44	39	35	44	39	35	32	26		
下方投影面積		cm ²	1.5	65	57	50	45	61	54	48	43	54	48	43	39	47	42	38	35	28			
等価発光面積		cm ²	2.0	70	63	57	52	66	59	54	49	58	53	48	45	51	47	43	40	33			
取付 高さ	器具間隔最大限		2.5	73	66	61	57	69	63	58	54	61	56	52	49	53	50	46	44	36			
	横方向 (A)	縦方向 (B)	3.0	75	69	64	60	71	66	61	57	63	59	55	52	55	52	49	46	38			
H m	1.38 H m	1.37 H m	4.0	78	73	69	65	74	69	66	62	65	62	59	56	58	55	53	50	41			
			5.0	80	76	72	69	75	72	69	66	67	64	62	59	59	57	55	53	43			
			7.0	82	79	76	73	78	75	72	70	69	67	65	63	61	60	58	56	46			
			10.0	84	81	79	77	79	77	75	73	71	69	68	66	63	62	60	59	49			

