

| 屋内照明器具特性 |                                          |
|----------|------------------------------------------|
| 品番 (品名)  | L G S 3 0 0 5 L                          |
| 光源       | LDA13L - G / Z100E / S / W ×1 1520.0 l m |
| 管理番号     | K0172136 ( 0 ) DB 1                      |
| B Z 分類   | BZ6                                      |

| 器具効率             |        | 61 %<br><br>上方光束<br>18 %<br>下方光束<br>43 % | 反射率  | 天井   | 80 %              |    |    |    |    | 70 % |    |    |    |    | 50 % |    |    |    |    | 30 % |    |    |    |    | 0 % |
|------------------|--------|------------------------------------------|------|------|-------------------|----|----|----|----|------|----|----|----|----|------|----|----|----|----|------|----|----|----|----|-----|
|                  |        |                                          |      | 壁    | 70                | 50 | 30 | 10 | 70 | 50   | 30 | 10 | 70 | 50 | 30   | 10 | 70 | 50 | 30 | 10   | 70 | 50 | 30 | 10 | 0 % |
|                  |        |                                          |      | 床    | 10 %              |    |    |    |    | 10 % |    |    |    |    | 10 % |    |    |    |    | 10 % |    |    |    |    | 0 % |
|                  |        |                                          |      | 室指数  | 照明率 ( X0.01 ) ZCM |    |    |    |    |      |    |    |    |    |      |    |    |    |    |      |    |    |    |    |     |
| 保守率              |        | 良<br>中<br>否                              | 0.67 | 0.6  | 30                | 23 | 18 | 15 | 28 | 22   | 17 | 14 | 25 | 20 | 16   | 13 | 22 | 18 | 14 | 12   | 10 |    |    |    |     |
|                  |        |                                          | 0.63 | 0.8  | 36                | 28 | 23 | 20 | 34 | 27   | 22 | 19 | 30 | 24 | 21   | 18 | 26 | 22 | 19 | 16   | 13 |    |    |    |     |
|                  |        |                                          | 1.0  | 39   | 33                | 28 | 24 | 37 | 31 | 26   | 23 | 33 | 28 | 24 | 21   | 29 | 25 | 22 | 20 | 16   |    |    |    |    |     |
|                  |        |                                          | 0.56 | 1.25 | 43                | 36 | 32 | 28 | 40 | 35   | 30 | 27 | 36 | 31 | 28   | 25 | 32 | 28 | 25 | 23   | 19 |    |    |    |     |
| 下方投影面積<br>等価発光面積 |        | cm <sup>2</sup><br><br>cm <sup>2</sup>   | 1.5  | 45   | 39                | 35 | 31 | 43 | 37 | 33   | 30 | 38 | 34 | 30 | 28   | 34 | 30 | 28 | 25 | 21   |    |    |    |    |     |
|                  |        |                                          | 2.0  | 49   | 44                | 39 | 36 | 46 | 41 | 38   | 35 | 41 | 38 | 34 | 32   | 37 | 34 | 31 | 29 | 24   |    |    |    |    |     |
|                  |        |                                          | 2.5  | 51   | 46                | 43 | 39 | 48 | 44 | 41   | 38 | 43 | 40 | 37 | 35   | 39 | 36 | 34 | 32 | 27   |    |    |    |    |     |
|                  |        |                                          | 3.0  | 52   | 48                | 45 | 42 | 50 | 46 | 43   | 40 | 45 | 42 | 39 | 37   | 40 | 38 | 36 | 34 | 29   |    |    |    |    |     |
| Hm               | 1.52Hm | 1.52Hm                                   | 4.0  | 54   | 51                | 48 | 46 | 52 | 49 | 46   | 44 | 47 | 44 | 42 | 40   | 42 | 40 | 38 | 37 | 31   |    |    |    |    |     |
|                  |        |                                          | 5.0  | 56   | 53                | 50 | 48 | 53 | 50 | 48   | 46 | 48 | 46 | 44 | 42   | 43 | 41 | 40 | 39 | 33   |    |    |    |    |     |
|                  |        |                                          | 7.0  | 57   | 55                | 53 | 51 | 54 | 53 | 51   | 49 | 49 | 48 | 46 | 45   | 45 | 43 | 42 | 41 | 35   |    |    |    |    |     |
|                  |        |                                          | 10.0 | 58   | 57                | 55 | 54 | 56 | 54 | 53   | 51 | 51 | 49 | 48 | 47   | 46 | 45 | 44 | 43 | 37   |    |    |    |    |     |

