

屋内照明器具特性	
品番 (品名)	LGB87078K
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 lm
管理番号	K0175931 (0) DR 1
BZ分類	BZ9

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		36 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		37 %																						
保守率		良 中 否	0.63	0.6	32	23	17	13	29	21	15	12	24	17	13	10	19	14	10	8	4			
			0.6	0.8	38	29	22	18	35	26	21	17	28	22	17	14	23	18	14	11	6			
				1.0	42	33	27	22	38	31	25	20	31	25	21	17	25	20	17	14	8			
			0.56	1.25	46	38	31	27	42	35	29	25	35	29	24	21	28	23	20	17	10			
下方投影面積		cm ²		1.5	49	41	35	30	45	38	32	28	37	32	27	24	30	26	22	19	12			
等価発光面積			cm ²	2.0	53	46	41	36	49	43	38	33	40	36	32	28	33	29	26	23	15			
取付 高さ	器具間隔最大限		2.5	56	50	45	40	51	46	41	37	43	38	35	32	35	31	29	26	17				
	横方向 (A)		縦方向 (B)	3.0	58	52	48	43	53	48	44	40	45	41	37	34	36	33	31	28	19			
H _m	1.66 H _m	2.08 H _m	4.0	60	56	52	48	56	52	48	45	47	44	41	38	39	36	34	32	22				
			5.0	62	58	55	51	57	54	51	48	48	46	43	41	40	38	36	34	24				
			7.0	64	61	58	56	60	57	54	52	50	48	46	44	42	40	39	37	26				
			10.0	66	64	61	59	61	59	57	55	52	50	49	47	44	42	41	40	28				

