

屋内照明器具特性

品番 (品名)	S C 4 3 0									
光源	LDA5 L - D - G - E17 / S / Z4 x1 440.0 l m									
管理番号	K0157700 (0) DB 1									
B Z 分類	B Z 9									

器具効率		9 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		5 7 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		3 5 %																					
保守率		良	0 . 6 3	0 . 6	4 0	2 9	2 2	1 7	3 6	2 6	2 0	1 5	2 8	2 1	1 6	1 2	2 1	1 6	1 2	9	4		
		中	0 . 6	0 . 8	4 8	3 7	2 9	2 4	4 3	3 3	2 7	2 2	3 4	2 6	2 1	1 7	2 5	2 0	1 6	1 3	6		
		否	0 . 5 6	1 . 0	5 3	4 3	3 5	3 0	4 8	3 9	3 2	2 7	3 8	3 1	2 6	2 2	2 8	2 3	1 9	1 6	8		
		1 . 2 5	5 8	4 8	4 1	3 5	5 2	4 4	3 7	3 2	4 1	3 5	3 0	2 6	3 1	2 7	2 3	2 0	1 0				
下方投影面積		c m ²		1 . 5	6 2	5 3	4 6	4 0	5 6	4 8	4 2	3 6	4 4	3 8	3 3	2 9	3 4	2 9	2 6	2 3	1 2		
等価発光面積		c m ²		2 . 0	6 7	5 9	5 3	4 7	6 0	5 4	4 8	4 3	4 8	4 3	3 9	3 5	3 7	3 3	3 0	2 7	1 4		
取付高さ	器具間隔最大限			2 . 5	7 0	6 3	5 7	5 2	6 4	5 7	5 2	4 8	5 1	4 6	4 2	3 9	3 9	3 6	3 3	3 0	1 7		
	横方向 (A)		縦方向 (B)	3 . 0	7 3	6 6	6 1	5 6	6 6	6 0	5 6	5 1	5 3	4 9	4 5	4 2	4 1	3 8	3 5	3 2	1 8		
H m	0 . 0 0 H m	0 . 0 0 H m	4 . 0	7 6	7 1	6 6	6 2	6 9	6 4	6 0	5 7	5 5	5 2	4 9	4 6	4 3	4 0	3 8	3 6	2 1			
			5 . 0	7 8	7 3	6 9	6 6	7 1	6 7	6 3	6 0	5 7	5 4	5 2	4 9	4 5	4 2	4 0	3 8	2 3			
			7 . 0	8 0	7 7	7 3	7 0	7 3	7 0	6 7	6 5	5 9	5 7	5 5	5 3	4 7	4 5	4 3	4 2	2 5			
			1 0 . 0	8 2	7 9	7 7	7 5	7 5	7 3	7 0	6 8	6 1	5 9	5 8	5 6	4 8	4 7	4 6	4 4	2 7			

