

屋内照明器具特性	
品番 (品名)	L G W8 5 0 8 1 S U
光源	L D A 5 L - D - G - E 1 7 / S / Z 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 7 5 9 3 8 (0) D R 1
B Z 分類	B Z 7 / 4 . 5 / B Z 6 / 6 . 0 / B Z 7 / 8 . 5 / B Z 6

器具効率		6 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		3 3 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		3 6 %																				
保守率		良 中 否	0 . 6 3	0 . 6	3 2	2 4	1 8	1 4	2 9	2 2	1 7	1 4	2 5	1 9	1 5	1 2	2 0	1 5	1 2	1 0	6	
			0 . 6	0 . 8	3 8	3 0	2 4	2 0	3 5	2 8	2 2	1 9	2 9	2 3	1 9	1 6	2 4	2 0	1 6	1 4	9	
			0 . 5 6	1 . 0	4 2	3 4	2 9	2 4	3 9	3 2	2 7	2 3	3 2	2 7	2 3	2 0	2 7	2 3	1 9	1 7	1 2	
				1 . 2 5	4 6	3 9	3 3	2 9	4 2	3 6	3 1	2 7	3 5	3 0	2 7	2 3	2 9	2 5	2 2	2 0	1 4	
下方投影面積		c m ²		1 . 5	4 8	4 2	3 7	3 2	4 5	3 9	3 4	3 0	3 8	3 3	2 9	2 6	3 1	2 8	2 5	2 2	1 6	
等価発光面積			c m ²	2 . 0	5 2	4 7	4 2	3 8	4 8	4 3	3 9	3 5	4 1	3 7	3 4	3 1	3 4	3 1	2 8	2 6	1 9	
取付 高さ	器具間隔最大限			2 . 5	5 5	5 0	4 5	4 2	5 1	4 6	4 2	3 9	4 3	4 0	3 7	3 4	3 6	3 3	3 1	2 9	2 1	
	横方向 (A) 縦方向 (B)			3 . 0	5 7	5 2	4 8	4 5	5 2	4 8	4 5	4 2	4 5	4 1	3 9	3 6	3 7	3 5	3 3	3 1	2 2	
H m	1 . 2 9 H m 1 . 7 2 H m			4 . 0	5 9	5 5	5 2	4 9	5 5	5 1	4 8	4 6	4 7	4 4	4 2	4 0	3 9	3 7	3 5	3 4	2 5	
				5 . 0	6 0	5 7	5 4	5 2	5 6	5 3	5 1	4 8	4 8	4 6	4 4	4 2	4 0	3 9	3 7	3 6	2 6	
				7 . 0	6 2	6 0	5 7	5 5	5 8	5 6	5 4	5 2	5 0	4 8	4 6	4 5	4 2	4 1	3 9	3 8	2 8	
				1 0 . 0	6 3	6 2	6 0	5 8	5 9	5 7	5 6	5 4	5 1	5 0	4 8	4 7	4 3	4 2	4 1	4 0	3 0	

