

屋内照明器具特性	
品番 (品名)	L G W8 5 2 8 1 B Z
光源	L D A 5 L - D - G - E 1 7 / S / Z 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 7 5 9 4 0 (0) D R 1
B Z 分類	B Z 7 / 0 . 9 / B Z 6

器具効率		7 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		3 2 % 3 8 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 3	0 . 6	0 . 6	3 3	2 4	1 9	1 5	3 0	2 2	1 7	1 4	2 5	1 9	1 5	1 2	2 1	1 6	1 3	1 0	7
			0 . 6	0 . 8	3 9	3 0	2 5	2 1	3 6	2 8	2 3	1 9	3 0	2 4	2 0	1 7	2 5	2 0	1 7	1 5	1 0	
			0 . 5 6	1 . 0	4 3	3 5	2 9	2 5	4 0	3 3	2 7	2 4	3 3	2 8	2 4	2 1	2 8	2 4	2 0	1 8	1 3	
			1 . 2 5	4 7	3 9	3 4	3 0	4 3	3 7	3 2	2 8	3 7	3 1	2 8	2 4	3 0	2 7	2 3	2 1	1 5		
下方投影面積		c m ²	1 . 5	5 0	4 3	3 8	3 3	4 6	4 0	3 5	3 1	3 9	3 4	3 0	2 7	3 2	2 9	2 6	2 3	2 1	1 7	
等価発光面積			c m ²	2 . 0	5 3	4 8	4 3	3 9	5 0	4 4	4 0	3 7	4 2	3 8	3 5	3 2	3 5	3 2	3 0	2 7	2 0	
取付 高さ	器具間隔最大限		2 . 5	5 6	5 1	4 6	4 3	5 2	4 7	4 4	4 0	4 4	4 1	3 8	3 5	3 7	3 5	3 2	3 0	2 2		
	横方向 (A) 縦方向 (B)		3 . 0	5 8	5 3	4 9	4 6	5 4	5 0	4 6	4 3	4 6	4 3	4 0	3 8	3 9	3 6	3 4	3 2	2 4		
H m	1 . 2 8 H m 1 . 7 3 H m		4 . 0	6 0	5 6	5 3	5 0	5 6	5 3	5 0	4 7	4 8	4 5	4 3	4 1	4 1	3 9	3 7	3 5	2 6		
			5 . 0	6 1	5 8	5 5	5 3	5 7	5 4	5 2	5 0	4 9	4 7	4 5	4 3	4 2	4 0	3 9	3 7	2 8		
			7 . 0	6 3	6 1	5 8	5 6	5 9	5 7	5 5	5 3	5 1	4 9	4 8	4 6	4 3	4 2	4 1	4 0	3 0		
			1 0 . 0	6 5	6 3	6 1	5 9	6 0	5 9	5 7	5 6	5 2	5 1	5 0	4 9	4 5	4 4	4 3	4 2	3 2		

