

屋内照明器具特性	
品番 (品名)	L G W8 0 3 2 0 K
光源	LED5000_70_317 x1 317.0 lm
管理番号	K0146954 (0) DB 1
B Z 分類	BZ6 / 0.7 / BZ5 / 3.5 / BZ6 / 4.5 / BZ5 / 6.0 / BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.63	0.6	51	39	31	26	48	37	30	25	43	34	28	24	39	31	26	22	18
			0.6	0.8	60	49	41	35	57	47	39	34	51	43	36	32	46	39	33	29	25
			0.56	1.0	67	56	48	42	63	53	46	41	56	48	43	38	50	44	39	35	30
				1.25	72	62	55	49	69	60	53	47	61	54	49	44	55	49	44	41	34
下方投影面積 等価発光面積		cm ²	1.5	76	67	60	54	72	64	58	52	65	58	53	49	58	53	48	45	38	
			2.0	82	74	68	62	78	71	65	60	70	64	59	55	63	58	54	51	43	
			2.5	85	78	73	68	81	75	70	65	73	68	64	60	66	62	58	55	47	
			3.0	88	82	76	72	83	78	73	69	75	71	67	64	68	64	61	58	50	
H _m	1.31 H _m	1.32 H _m	4.0	91	86	82	78	87	82	78	75	78	75	72	69	71	68	65	63	54	
			5.0	93	89	85	81	88	85	81	78	80	77	74	72	72	70	68	66	56	
			7.0	95	92	89	86	91	88	85	83	82	80	78	76	75	73	71	69	60	
			10.0	97	95	92	90	93	90	88	86	84	83	81	79	76	75	74	72	62	

