

屋内照明器具特性	
品番 (品名)	L G W C 8 1 3 1 0 K
光源	LED2700_70_243 ×1 243.0 l m
管理番号	K0149622 (0) DR 1
B Z 分類	B Z 9

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		5 0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		5 0 %																					
保守率		良 中 否	0 . 6 3	0 . 6	4 4	3 1	2 3	1 7	4 0	2 9	2 1	1 6	3 3	2 4	1 8	1 3	2 6	1 9	1 4	1 0	5		
			0 . 6	0 . 8	5 2	3 9	3 1	2 5	4 7	3 6	2 8	2 3	3 9	3 0	2 4	1 9	3 1	2 4	1 9	1 5	8		
			0 . 5 6	1 . 0	5 8	4 6	3 7	3 0	5 3	4 2	3 4	2 8	4 3	3 5	2 8	2 3	3 4	2 8	2 3	1 9	1 1		
				1 . 2 5	6 3	5 2	4 3	3 7	5 8	4 8	4 0	3 4	4 7	3 9	3 3	2 8	3 8	3 2	2 7	2 3	1 4		
下方投影面積		c m ²		1 . 5	6 7	5 7	4 8	4 2	6 1	5 2	4 5	3 9	5 0	4 3	3 7	3 2	4 0	3 5	3 0	2 6	1 6		
等価発光面積			c m ²	2 . 0	7 3	6 4	5 6	5 0	6 7	5 8	5 2	4 6	5 5	4 9	4 3	3 9	4 4	3 9	3 5	3 1	2 0		
取付 高さ	器具間隔最大限			2 . 5	7 7	6 8	6 1	5 5	7 0	6 3	5 7	5 1	5 8	5 3	4 8	4 3	4 7	4 3	3 9	3 5	2 3		
	横方向 (A)		縦方向 (B)	3 . 0	7 9	7 2	6 5	6 0	7 3	6 6	6 0	5 5	6 1	5 5	5 1	4 7	4 9	4 5	4 2	3 8	2 5		
H m	1 . 3 8 H m	1 . 3 0 H m		4 . 0	8 3	7 7	7 1	6 6	7 6	7 1	6 6	6 1	6 4	6 0	5 6	5 2	5 2	4 9	4 6	4 3	2 9		
				5 . 0	8 5	8 0	7 5	7 0	7 9	7 4	6 9	6 5	6 6	6 2	5 9	5 6	5 4	5 1	4 9	4 6	3 1		
				7 . 0	8 8	8 4	8 0	7 6	8 2	7 8	7 4	7 1	6 9	6 6	6 3	6 0	5 7	5 4	5 2	5 0	3 5		
				1 0 . 0	9 0	8 7	8 4	8 1	8 4	8 1	7 8	7 5	7 1	6 9	6 7	6 4	5 9	5 7	5 5	5 4	3 8		

