

屋内照明器具特性	
品番 (品名)	L G W8 0 3 2 7 K
光源	LED5000_70_272 x1 272.0 l m
管理番号	K0146941 (0) DB 1
B Z 分類	B Z 6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	49	37	29	24	46	35	28	23	41	31	25	21	36	28	23	19	15
			0.6	0.8	58	46	38	32	55	44	36	31	48	39	33	28	42	35	30	26	21
			0.56	1.0	64	53	45	39	60	50	43	37	53	45	39	34	47	40	35	31	25
				1.25	70	59	52	45	66	56	49	44	58	50	45	40	51	45	40	36	29
下方投影面積		cm ²		1.5	74	64	57	51	70	61	54	49	62	55	49	44	54	49	44	40	33
			等価発光面積	cm ²	2.0	79	71	64	59	75	67	61	56	66	60	55	51	59	54	50	46
取付 高さ	器具間隔最大限			2.5	83	76	69	64	78	72	66	61	70	64	60	56	61	57	54	50	41
	横方向 (A) 縦方向 (B)			3.0	86	79	73	68	81	75	70	65	72	67	63	59	64	60	57	54	44
H m	1.37 H m	1.37 H m	4.0	89	83	79	74	84	79	75	71	75	71	68	64	67	63	61	58	48	
			5.0	91	86	82	78	86	82	78	75	77	74	71	68	69	66	63	61	51	
			7.0	93	90	86	83	89	85	82	79	80	77	74	72	71	69	67	65	54	
			10.0	95	93	90	88	91	88	86	84	82	80	78	76	73	71	70	68	57	

