

屋内照明器具特性	
品番 (品名)	L G W8 0 3 1 7 K
光源	LED2700_70_205 ×1 205.0 l m
管理番号	K0146940 (0) DB 1
B Z 分類	BZ6 / 3.5 / BZ7

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
					床	10 %				10 %				10 %				10 %				0 %	
						室指数																	
上方光束		27 %	照明率 (X0.01)																			Z CM	
下方光束		73 %																					
保守率		良 中 否	0.63	0.6	49	37	29	23	47	35	28	22	41	32	25	21	37	29	23	19	15		
			0.6	0.8	58	46	38	32	55	44	36	30	49	40	33	28	43	36	30	26	21		
			0.56	1.0	64	53	44	38	61	50	42	37	54	45	39	34	48	41	35	31	26		
				1.25	70	59	51	44	66	56	49	43	59	51	45	40	52	46	41	36	30		
下方投影面積		cm ²	1.5	74	64	56	50	70	61	53	48	62	55	49	44	55	49	44	40	34			
等価発光面積			cm ²	2.0	79	70	63	57	75	67	61	55	67	61	55	51	60	55	50	46	39		
取付 高さ	器具間隔最大限		2.5	83	75	68	63	79	71	65	60	71	65	60	55	63	58	54	51	43			
	横方向 (A)		縦方向 (B)	3.0	85	78	72	67	81	75	69	64	73	68	63	59	65	61	57	54	46		
H m	1.33 H m	1.34 H m	4.0	89	83	78	73	84	79	74	70	76	72	68	64	68	65	62	59	50			
			5.0	91	86	81	77	87	82	78	74	78	74	71	68	70	67	65	62	53			
			7.0	94	90	86	82	89	86	82	79	81	78	75	73	73	71	68	66	57			
			10.0	96	93	90	87	91	89	86	83	83	81	79	77	75	74	72	70	60			

