

屋内照明器具特性	
品番 (品名)	L G W8 0 3 3 5 K
光源	LED5000_70_329 ×1 329.0 l m
管理番号	K0146950 (0) DB 1
B Z 分類	B Z 6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		2 8 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		7 2 %																				
保守率		良 中 否	0 . 6 3	0 . 6	4 9	3 7	2 8	2 3	4 6	3 5	2 7	2 2	4 1	3 2	2 5	2 0	3 6	2 8	2 3	1 9	1 5	
			0 . 6	0 . 8	5 8	4 6	3 7	3 1	5 5	4 4	3 6	3 0	4 9	3 9	3 3	2 8	4 3	3 6	3 0	2 6	2 1	
			0 . 5 6	1 . 0	6 4	5 2	4 4	3 8	6 1	5 0	4 2	3 6	5 4	4 5	3 9	3 4	4 8	4 1	3 5	3 1	2 5	
				1 . 2 5	7 0	5 9	5 1	4 4	6 6	5 6	4 9	4 3	5 9	5 1	4 4	3 9	5 2	4 6	4 0	3 6	3 0	
下方投影面積		c m ²	1 . 5	7 4	6 4	5 6	5 0	7 0	6 1	5 3	4 8	6 2	5 5	4 9	4 4	5 5	4 9	4 4	4 0	3 3		
等価発光面積			c m ²	2 . 0	7 9	7 1	6 3	5 7	7 5	6 7	6 1	5 5	6 7	6 1	5 5	5 1	6 0	5 5	5 0	4 6	3 9	
取付 高さ	器具間隔最大限		2 . 5	8 3	7 5	6 9	6 3	7 9	7 2	6 6	6 0	7 0	6 5	6 0	5 6	6 3	5 8	5 4	5 1	4 3		
	横方向 (A) 縦方向 (B)		3 . 0	8 5	7 8	7 2	6 7	8 1	7 5	6 9	6 5	7 3	6 8	6 3	5 9	6 5	6 1	5 7	5 4	4 6		
H m	1 . 4 0 H m	1 . 4 0 H m	4 . 0	8 9	8 3	7 8	7 3	8 5	7 9	7 5	7 0	7 6	7 2	6 8	6 5	6 8	6 5	6 2	5 9	5 0		
			5 . 0	9 1	8 6	8 2	7 7	8 7	8 2	7 8	7 4	7 8	7 5	7 1	6 8	7 0	6 8	6 5	6 2	5 3		
			7 . 0	9 4	9 0	8 6	8 3	8 9	8 6	8 3	7 9	8 1	7 8	7 5	7 3	7 3	7 1	6 9	6 7	5 7		
			1 0 . 0	9 6	9 3	9 0	8 7	9 2	8 9	8 6	8 4	8 3	8 1	7 9	7 7	7 5	7 4	7 2	7 0	6 0		

