

屋内照明器具特性	
品番 (品名)	L G W C 4 7 0 2 0
光源	L L D 2 0 0 0 M L C B 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 6 3 4 2 (0) D R 1
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2

器具効率		62 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		62 %																							
保守率		良 中 否	0 . 63	0 . 6	40	34	30	27	39	33	29	27	38	33	29	27	37	32	29	27	25				
			0 . 6	0 . 8	47	41	37	34	46	40	37	34	44	40	36	34	43	39	36	34	32				
				1 . 0	51	45	42	39	50	45	41	39	48	44	41	39	47	43	41	38	37				
			0 . 56	1 . 25	54	49	46	43	53	49	46	43	52	48	45	43	50	47	45	43	41				
下方投影面積		c m ²		1 . 5	56	52	49	46	55	51	49	46	54	50	48	46	52	50	47	45	44				
等価発光面積			c m ²	2 . 0	59	56	53	51	58	55	53	50	56	54	52	50	55	53	51	49	48				
取付 高さ	器具間隔最大限		2 . 5	61	58	55	53	60	57	55	53	58	56	54	53	57	55	53	52	51					
	横方向 (A)		縦方向 (B)		3 . 0	62	59	57	55	61	59	57	55	59	57	56	54	58	56	55	54	52			
H m	1 . 17 H m	1 . 17 H m	4 . 0	63	61	60	58	62	61	59	58	61	59	58	57	59	58	57	56	55					
			5 . 0	64	62	61	60	63	62	60	59	62	60	59	58	60	59	58	58	56					
			7 . 0	65	64	63	62	64	63	62	61	63	62	61	60	61	60	60	59	58					
			10 . 0	66	65	64	63	65	64	63	63	63	63	62	62	62	61	61	60	59					

