

屋内照明器具特性

| | | |
|---------|--------------------|-----------|
| 品番 (品名) | LGBZ2427 | |
| 光源 | LED6200_70_4650 x1 | 4650.0 lm |
| 管理番号 | K0161808(0)D 1 | |
| BZ分類 | BZ6/0.7/BZ5 | |

| | | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|-------------|------|-----|----|-----|-----|----|----|-----|----|----|----|-----|----|----|----|----|----|-----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | | |
| | 上方光束 3% | | 下方光束 97% | 反射率 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.63 | 0.6 | 53 | 41 | 32 | 27 | 52 | 40 | 32 | 26 | 49 | 38 | 31 | 26 | 47 | 37 | 31 | 26 | 24 | |
| | 中 | 0.6 | 0.8 | 63 | 51 | 43 | 37 | 62 | 50 | 42 | 36 | 59 | 49 | 41 | 36 | 56 | 47 | 41 | 36 | 33 | |
| | 否 | 0.56 | 1.0 | 70 | 59 | 50 | 44 | 68 | 58 | 50 | 44 | 65 | 56 | 49 | 43 | 62 | 54 | 48 | 43 | 40 | |
| | | | | 1.25 | 76 | 66 | 58 | 52 | 74 | 65 | 57 | 51 | 71 | 62 | 56 | 50 | 67 | 60 | 54 | 50 | 47 |
| 下方投影面積 | cm ² | | 1.5 | 81 | 71 | 63 | 57 | 79 | 70 | 63 | 57 | 75 | 67 | 61 | 56 | 71 | 65 | 60 | 55 | 52 | |
| 等価発光面積 | cm ² | | 2.0 | 86 | 78 | 71 | 66 | 84 | 77 | 71 | 65 | 81 | 74 | 69 | 64 | 77 | 72 | 67 | 63 | 60 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 90 | 83 | 77 | 72 | 88 | 82 | 76 | 71 | 84 | 79 | 74 | 70 | 81 | 76 | 72 | 69 | 65 | |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 93 | 86 | 81 | 76 | 91 | 85 | 80 | 76 | 87 | 82 | 78 | 74 | 84 | 80 | 76 | 73 | 69 | |
| Hm | 1.46Hm | 1.46Hm | 4.0 | 96 | 91 | 87 | 82 | 94 | 90 | 85 | 82 | 91 | 87 | 83 | 80 | 87 | 84 | 81 | 78 | 75 | |
| | | | 5.0 | 98 | 94 | 90 | 87 | 96 | 92 | 89 | 86 | 93 | 90 | 87 | 84 | 90 | 87 | 84 | 82 | 78 | |
| | | | 7.0 | 101 | 97 | 94 | 92 | 99 | 96 | 93 | 91 | 96 | 93 | 91 | 88 | 92 | 90 | 88 | 86 | 83 | |
| | | | 10.0 | 103 | 100 | 98 | 96 | 101 | 99 | 97 | 95 | 98 | 96 | 94 | 92 | 95 | 93 | 92 | 90 | 86 | |

