

屋内照明器具特性	
品番 (品名)	L G W C 4 7 1 0 7
光源	L L D 2 0 0 0 L C B 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 6 3 4 1 (0) D R 1
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2

器具効率		68 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01)																	ZCM
保守率		良 中 否	0.63	0.6	44	37	32	29	43	36	32	29	42	36	32	29	40	35	32	29	28	
			0.6	0.8	51	45	40	37	50	44	40	37	48	43	40	37	47	43	39	37	35	
			0.56	1.0	55	50	46	42	54	49	45	42	53	48	45	42	51	47	44	42	41	
				1.25	59	54	50	47	58	53	50	47	56	52	49	47	55	51	49	46	45	
下方投影面積		cm ²	1.5	61	57	53	51	60	56	53	50	59	55	52	50	57	54	52	50	48		
等価発光面積				cm ²	2.0	64	61	58	55	63	60	57	55	62	59	56	54	60	58	56	54	53
取付高さ	器具間隔最大限				2.5	66	63	61	58	65	62	60	58	64	61	59	57	62	60	58	57	55
	横方向 (A)		縦方向 (B)		3.0	67	65	63	61	66	64	62	60	65	63	61	59	63	62	60	59	57
H m	1.17 H m	1.17 H m	4.0	69	67	65	63	68	66	64	63	66	65	63	62	65	63	62	61	60		
			5.0	70	68	67	65	69	67	66	65	67	66	65	64	66	65	64	63	61		
			7.0	71	70	68	67	70	69	68	67	68	67	67	66	67	66	65	65	63		
			10.0	72	71	70	69	71	70	69	68	69	68	68	67	68	67	67	66	64		

