

屋内照明器具特性	
品番 (品名)	L G W C 4 7 1 2 0
光源	L L D 4 0 0 0 M L C B 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 6 3 4 0 (0) D R 1
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2

器具効率		5 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 3	0 . 6	3 8	3 2	2 8	2 5	3 8	3 2	2 8	2 5	3 6	3 1	2 8	2 5	3 5	3 1	2 8	2 5	2 4
			0 . 6	0 . 8	4 4	3 9	3 5	3 2	4 4	3 8	3 5	3 2	4 2	3 8	3 5	3 2	4 1	3 7	3 4	3 2	3 1
			0 . 5 6	1 . 0	4 8	4 3	4 0	3 7	4 7	4 3	3 9	3 7	4 6	4 2	3 9	3 7	4 5	4 1	3 9	3 6	3 5
				1 . 2 5	5 1	4 7	4 4	4 1	5 1	4 7	4 3	4 1	4 9	4 6	4 3	4 1	4 8	4 5	4 2	4 0	3 9
下方投影面積		c m ²		1 . 5	5 3	5 0	4 7	4 4	5 3	4 9	4 6	4 4	5 1	4 8	4 6	4 4	5 0	4 7	4 5	4 3	4 2
				2 . 0	5 6	5 3	5 0	4 8	5 5	5 2	5 0	4 8	5 4	5 1	4 9	4 7	5 2	5 0	4 9	4 7	4 6
取付 高さ	器具間隔最大限			2 . 5	5 8	5 5	5 3	5 1	5 7	5 4	5 2	5 1	5 5	5 3	5 2	5 0	5 4	5 2	5 1	4 9	4 8
	横方向 (A) 縦方向 (B)			3 . 0	5 9	5 6	5 5	5 3	5 8	5 6	5 4	5 2	5 6	5 5	5 3	5 2	5 5	5 4	5 2	5 1	5 0
H m	1 . 1 7 H m	1 . 1 7 H m		4 . 0	6 0	5 8	5 7	5 5	5 9	5 8	5 6	5 5	5 8	5 6	5 5	5 4	5 6	5 5	5 4	5 3	5 2
				5 . 0	6 1	5 9	5 8	5 7	6 0	5 9	5 8	5 6	5 9	5 8	5 7	5 6	5 7	5 6	5 6	5 5	5 3
				7 . 0	6 2	6 1	6 0	5 9	6 1	6 0	5 9	5 8	6 0	5 9	5 8	5 7	5 8	5 8	5 7	5 6	5 5
				1 0 . 0	6 2	6 2	6 1	6 0	6 2	6 1	6 0	6 0	6 0	6 0	5 9	5 9	5 9	5 8	5 8	5 8	5 6

