

屋内照明器具特性	
品番 (品名)	L S E W4 0 5 4 K
光源	LED5000_70_382 ×1 382.0 l m
管理番号	K0160244 (0) DR 1
B Z 分類	BZ9

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		50 %	室指数	照明率 (X0.01)																			Z C M		
下方光束		50 %																							
保守率		良 中 否	0.63	0.6	44	32	24	18	40	29	22	17	33	24	18	14	26	19	14	11	6				
			0.6	0.8	52	40	32	25	48	37	29	23	39	30	24	20	31	25	20	16	9				
				1.0	58	46	38	31	53	43	35	29	44	35	29	24	35	28	24	20	12				
			0.56	1.25	64	53	44	38	58	48	41	35	48	40	34	29	38	32	28	24	15				
下方投影面積		cm ²		1.5	68	57	49	43	62	53	46	40	51	44	38	33	41	36	31	27	17				
等価発光面積			cm ²	2.0	74	64	57	51	67	59	53	47	56	50	44	40	45	40	36	33	21				
取付 高さ	器具間隔最大限			2.5	77	69	62	56	71	64	58	52	59	53	49	44	48	44	40	37	24				
	横方向 (A)		縦方向 (B)	3.0	80	73	66	61	74	67	61	57	61	56	52	48	50	46	43	40	27				
H m	1.88 H m	1.63 H m		4.0	83	77	72	67	77	72	67	62	65	60	57	53	53	50	47	44	30				
				5.0	86	81	76	72	79	75	70	66	67	63	60	57	55	52	50	47	33				
				7.0	89	84	81	77	82	78	75	72	69	67	64	61	57	55	53	51	36				
				10.0	91	88	85	82	84	81	79	76	72	69	67	65	60	58	56	55	39				

