

屋内照明器具特性	
品番 (品名)	L S E W C 4 0 2 7 K
光源	LED2700_70_300 ×1 300.0 l m
管理番号	K0146950 (0) DB 1
B Z 分類	B Z 6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		28 % 72 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.63	0.6	49	37	28	23	46	35	27	22	41	32	25	20	36	28	23	19	15	
			0.6	0.8	58	46	37	31	55	44	36	30	49	39	33	28	43	36	30	26	21	
			0.56	1.0	64	52	44	38	61	50	42	36	54	45	39	34	48	41	35	31	25	
				1.25	70	59	51	44	66	56	49	43	59	51	44	39	52	46	40	36	30	
下方投影面積		cm ²	1.5	74	64	56	50	70	61	53	48	62	55	49	44	55	49	44	40	33		
等価発光面積		cm ²	2.0	79	71	63	57	75	67	61	55	67	61	55	51	60	55	50	46	39		
取付 高さ	器具間隔最大限		2.5	83	75	69	63	79	72	66	60	70	65	60	56	63	58	54	51	43		
	横方向 (A) 縦方向 (B)		3.0	85	78	72	67	81	75	69	65	73	68	63	59	65	61	57	54	46		
H m	1.40 H m	1.40 H m	4.0	89	83	78	73	85	79	75	70	76	72	68	65	68	65	62	59	50		
			5.0	91	86	82	77	87	82	78	74	78	75	71	68	70	68	65	62	53		
			7.0	94	90	86	83	89	86	83	79	81	78	75	73	73	71	69	67	57		
			10.0	96	93	90	87	92	89	86	84	83	81	79	77	75	74	72	70	60		

