

屋内照明器具特性	
品番 (品名)	L S E W C 4 0 5 5 K
光源	LED5000_70_329 ×1 329.0 l m
管理番号	K0149624 (0) DR 1
B Z 分類	BZ9 / 0.9 / BZ8 / 1.1 / BZ9

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		5 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		5 0 %																				
保守率		良 中 否	0 . 6 3	0 . 6	4 5	3 2	2 4	1 9	4 1	3 0	2 2	1 7	3 3	2 5	1 9	1 4	2 7	2 0	1 5	1 2	6	
			0 . 6	0 . 8	5 3	4 1	3 2	2 6	4 8	3 7	3 0	2 4	4 0	3 1	2 5	2 0	3 2	2 5	2 0	1 6	1 0	
			0 . 5 6	1 . 0	5 9	4 7	3 8	3 2	5 4	4 3	3 5	3 0	4 4	3 6	3 0	2 5	3 5	2 9	2 4	2 0	1 2	
				1 . 2 5	6 4	5 3	4 5	3 8	5 9	4 9	4 1	3 5	4 8	4 1	3 5	3 0	3 9	3 3	2 8	2 4	1 5	
下方投影面積		c m ²		1 . 5	6 8	5 8	5 0	4 3	6 2	5 3	4 6	4 0	5 1	4 4	3 8	3 4	4 1	3 6	3 1	2 8	1 7	
			等価発光面積	c m ²	2 . 0	7 4	6 5	5 7	5 1	6 8	6 0	5 3	4 7	5 6	5 0	4 4	4 0	4 5	4 1	3 6	3 3	2 1
取付高さ	器具間隔最大限			2 . 5	7 7	6 9	6 2	5 7	7 1	6 4	5 8	5 3	5 9	5 4	4 9	4 5	4 8	4 4	4 0	3 7	2 4	
	横方向 (A) 縦方向 (B)			3 . 0	8 0	7 3	6 7	6 1	7 4	6 7	6 2	5 7	6 1	5 6	5 2	4 8	5 0	4 6	4 3	4 0	2 7	
H m	1 . 3 3 H m	1 . 5 2 H m		4 . 0	8 4	7 7	7 2	6 7	7 7	7 2	6 7	6 3	6 5	6 0	5 7	5 3	5 0	4 7	4 4	3 0		
				5 . 0	8 6	8 1	7 6	7 2	7 9	7 5	7 0	6 7	6 7	6 3	6 0	5 7	5 5	5 2	5 0	4 7	3 3	
				7 . 0	8 9	8 4	8 1	7 7	8 2	7 8	7 5	7 2	6 9	6 6	6 4	6 1	5 7	5 5	5 3	5 1	3 6	
				1 0 . 0	9 1	8 8	8 5	8 2	8 4	8 1	7 9	7 6	7 2	6 9	6 7	6 5	6 0	5 8	5 6	5 5	3 9	

