

屋内照明器具特性	
品番 (品名)	X S L A 1 0 1 L
光源	L L D 4 0 0 0 L S C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 5 6 3 7 (0) D R 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4

器具効率		86 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	50	40	33	29	49	39	33	29	47	38	33	29	45	38	32	28	27
			0.63	0.8	59	49	43	38	58	49	43	38	56	48	42	38	53	47	42	38	36
			0.56	1.0	65	56	50	45	64	55	49	45	61	54	49	44	59	53	48	44	42
				1.25	70	62	56	52	69	61	56	51	66	60	55	51	64	58	54	51	49
下方投影面積		cm ²		1.5	74	67	61	57	72	66	60	56	70	64	60	56	67	63	59	55	53
			等価発光面積		cm ²	2.0	78	73	68	64	77	72	67	63	75	70	66	63	72	68	65
取付高さ	器具間隔最大限		2.5	81	76	72	69	80	75	72	68	78	74	70	67	75	72	69	67	64	
	横方向 (A) 縦方向 (B)			3.0	83	79	75	72	82	78	75	72	80	76	73	71	77	75	72	70	68
H m	1.27 H m 1.27 H m		4.0	86	83	80	77	85	82	79	76	82	80	77	75	80	78	76	74	72	
			5.0	87	85	82	80	86	84	81	79	84	82	80	78	82	80	78	77	74	
			7.0	89	87	85	83	88	86	84	83	86	84	83	81	84	82	81	80	78	
			10.0	90	89	88	86	89	88	87	86	87	86	85	84	85	84	83	82	80	

