

屋内照明器具特性	
品番 (品名)	N N F W2 1 8 1 3 C
光源	LED3000_85_1390 ×1 1390.0 lm
管理番号	K0175590 (2) DR 1
B Z 分類	BZ6 / 1.4 / BZ5 / 2.3 / BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		19 %	室指数	照明率 (X0.01) Z C M																		
下方光束		81 %																				
保守率		良 中 否	0.83	0.6	52	39	31	26	49	38	30	25	45	35	29	24	41	33	27	23	19	
			0.81	0.8	61	49	41	35	58	47	40	34	53	44	37	32	48	41	35	31	27	
			0.77	1.0	67	56	48	42	64	54	46	41	59	50	44	39	54	46	41	37	32	
				1.25	73	63	55	49	70	60	53	47	64	56	50	45	59	52	47	43	38	
下方投影面積		cm ²	1.5	77	68	60	54	74	65	58	53	68	61	55	50	62	56	51	47	42		
等価発光面積		cm ²	2.0	83	75	68	62	79	72	66	61	73	67	62	57	67	62	58	54	48		
取付 高さ	器具間隔最大限		2.5	86	79	73	68	83	77	71	66	77	71	67	63	70	66	62	59	53		
	横方向 (A)	縦方向 (B)	3.0	89	83	77	72	86	80	75	70	79	74	70	66	73	69	66	63	56		
1.5m	2.15 m	1.93 m	4.0	92	87	83	79	89	84	80	76	82	78	75	72	76	73	70	68	61		
2	2.86	2.55	5.0	94	90	86	83	91	87	83	80	84	81	78	75	78	76	73	71	64		
2.5	3.59	3.16	7.0	97	94	90	88	93	90	88	85	87	84	82	80	81	79	77	75	67		
3	4.28	3.77	10.0	99	96	94	92	95	93	91	89	89	87	85	84	83	81	80	78	71		

