

屋内照明器具特性	
品番 (品名)	NNF W4 1 8 0 0 C
光源	LED5000_85_2210 ×1 2210.0 lm
管理番号	K0175592 (0) DR 1
B Z 分類	BZ6 / 1.1 / BZ5 / 2.8 / BZ6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		1 9 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		8 1 %																				
保守率		良 中 否	0 . 8 3	0 . 6	5 2	3 9	3 1	2 6	4 9	3 8	3 0	2 5	4 5	3 5	2 9	2 4	4 1	3 3	2 7	2 3	1 9	
			0 . 8 1	0 . 8	6 1	4 9	4 1	3 5	5 8	4 7	4 0	3 4	5 3	4 4	3 7	3 2	4 8	4 1	3 5	3 1	2 7	
			0 . 7 7	1 . 0	6 7	5 6	4 8	4 2	6 4	5 4	4 6	4 1	5 9	5 0	4 4	3 9	5 4	4 7	4 1	3 7	3 2	
				1 . 2 5	7 3	6 3	5 5	4 9	7 0	6 0	5 3	4 7	6 4	5 6	5 0	4 5	5 9	5 2	4 7	4 3	3 8	
下方投影面積		c m ²	1 . 5	7 7	6 8	6 0	5 4	7 4	6 5	5 8	5 3	6 8	6 1	5 5	5 0	6 2	5 6	5 1	4 7	4 2		
等価発光面積			c m ²	2 . 0	8 3	7 5	6 8	6 2	7 9	7 2	6 6	6 1	7 3	6 7	6 2	5 7	6 7	6 2	5 8	5 4	4 8	
取付 高さ	器具間隔最大限		2 . 5	8 6	7 9	7 3	6 8	8 3	7 7	7 1	6 6	7 6	7 1	6 7	6 3	7 0	6 6	6 2	5 9	5 3		
	横方向 (A) 縦方向 (B)		3 . 0	8 9	8 3	7 7	7 2	8 6	8 0	7 5	7 0	7 9	7 4	7 0	6 6	7 3	6 9	6 6	6 3	5 6		
1 . 5 m	2 . 1 8 m	2 . 0 9 m	4 . 0	9 2	8 7	8 3	7 9	8 9	8 4	8 0	7 6	8 2	7 8	7 5	7 2	7 6	7 3	7 0	6 8	6 1		
2	2 . 8 7	2 . 6 6	5 . 0	9 4	9 0	8 6	8 3	9 1	8 7	8 3	8 0	8 4	8 1	7 8	7 5	7 8	7 6	7 3	7 1	6 4		
2 . 5	3 . 5 7	3 . 2 4	7 . 0	9 7	9 4	9 0	8 8	9 3	9 0	8 8	8 5	8 7	8 4	8 2	8 0	8 1	7 9	7 7	7 5	6 7		
3	4 . 2 7	3 . 8 4	1 0 . 0	9 9	9 6	9 4	9 2	9 5	9 3	9 1	8 9	8 9	8 7	8 5	8 4	8 3	8 1	8 0	7 8	7 1		

