

屋内照明器具特性	
品番 (品名)	N N F S 2 1 8 7 0 C
光源	LED3000_85_1390 ×1 1390.0 lm
管理番号	K0175588 (0) DR 1
B Z 分類	BZ6 / 1.1 / BZ5 / 3.5 / BZ6 / 4.5 / BZ5 / 6.0 / BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.83	0.6	52	39	31	26	49	38	30	25	45	35	29	24	41	33	27	23	20
			0.81	0.8	61	49	41	35	58	47	40	34	53	44	37	32	49	41	35	31	27
			0.77	1.0	67	56	48	42	64	54	47	41	59	50	44	39	54	47	41	37	32
				1.25	73	63	55	49	70	61	53	48	64	56	50	45	59	52	47	43	38
下方投影面積		cm ²		1.5	77	68	60	54	74	65	58	53	68	61	55	50	62	56	52	47	42
			等価発光面積	cm ²	2.0	83	75	68	63	80	72	66	61	73	67	62	58	67	62	58	54
取付 高さ	器具間隔最大限			2.5	87	79	73	68	83	77	71	66	77	71	67	63	71	66	63	59	53
	横方向 (A)	縦方向 (B)		3.0	89	83	77	73	86	80	75	71	79	75	70	67	73	69	66	63	56
1.5m	2.15 m	1.93 m		4.0	92	87	83	79	89	84	80	76	83	79	75	72	76	73	70	68	61
2	2.86	2.54		5.0	95	90	86	83	91	87	84	80	85	81	78	76	78	76	73	71	64
2.5	3.59	3.16		7.0	97	94	91	88	94	91	88	85	87	85	82	80	81	79	77	75	68
3	4.28	3.76		10.0	99	96	94	92	96	93	91	89	89	87	85	84	83	82	80	79	71

