

屋内照明器具特性	
品番 (品名)	P A 8 1 0 0 1 U P W P M 4 0
光源	L E D 4 0 0 0 _ 7 0 _ 6 8 5 × 1 6 8 5 . 0 l m
管理番号	K 0 1 6 7 0 3 3 (0) D B 1
B Z 分類	B Z 1 0

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		0 %																					
保守率		良 中 否	0 . 6 9	0 . 6	4 3	3 3	2 6	2 2	3 7	2 8	2 3	1 9	2 5	1 9	1 6	1 3	1 4	1 1	9	8	0		
			0 . 6 7	0 . 8	5 1	4 1	3 4	2 9	4 3	3 5	3 0	2 5	2 9	2 4	2 1	1 8	1 7	1 4	1 2	1 1	0		
			0 . 6 3	1 . 0	5 6	4 7	4 0	3 5	4 8	4 1	3 5	3 1	3 3	2 8	2 4	2 2	1 9	1 6	1 4	1 3	0		
				1 . 2 5	6 1	5 3	4 7	4 2	5 2	4 6	4 0	3 6	3 6	3 1	2 8	2 6	2 0	1 8	1 6	1 5	0		
下方投影面積		c m ²	1 . 5	6 5	5 7	5 1	4 7	5 6	4 9	4 4	4 0	3 8	3 4	3 1	2 9	2 2	2 0	1 8	1 7	0			
等価発光面積			c m ²	2 . 0	7 0	6 3	5 8	5 4	6 0	5 5	5 0	4 7	4 1	3 8	3 5	3 3	2 4	2 2	2 1	1 9	0		
取付 高さ	器具間隔最大限		2 . 5	7 3	6 7	6 3	5 9	6 3	5 8	5 4	5 1	4 3	4 0	3 8	3 6	2 5	2 3	2 2	2 1	0			
	横方向 (A)		縦方向 (B)	3 . 0	7 5	7 0	6 6	6 3	6 5	6 1	5 7	5 4	4 4	4 2	4 0	3 8	2 6	2 4	2 3	2 2	0		
1 . 5m	0 . 3 m	0 . 3 m	4 . 0	7 8	7 4	7 1	6 8	6 7	6 4	6 1	5 9	4 6	4 4	4 3	4 1	2 7	2 6	2 5	2 4	0			
2	0 . 4	0 . 4	5 . 0	8 0	7 6	7 3	7 1	6 9	6 6	6 4	6 1	4 7	4 6	4 4	4 3	2 7	2 7	2 6	2 5	0			
2 . 5	0 . 5	0 . 5	7 . 0	8 2	7 9	7 7	7 5	7 0	6 8	6 7	6 5	4 9	4 8	4 6	4 5	2 8	2 8	2 7	2 7	0			
3	0 . 6	0 . 6	1 0 . 0	8 3	8 1	8 0	7 8	7 2	7 0	6 9	6 8	5 0	4 9	4 8	4 7	2 9	2 9	2 8	2 8	0			

