

屋内照明器具特性	
品番 (品名)	LGC51125
光源	LED6200_70_5200 x1 5200.0lm
管理番号	K0168481(0)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	7%	床	10%				10%				10%				10%				0%				
下方光束	93%	室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	5.4	4.2	3.4	2.8	5.2	4.1	3.3	2.8	4.9	3.9	3.2	2.7	4.7	3.8	3.1	2.7	2.4			
	中	0.6	0.8	6.4	5.2	4.4	3.8	6.2	5.1	4.4	3.8	5.9	4.9	4.2	3.7	5.5	4.7	4.1	3.7	3.4			
	否	0.56	1.0	7.1	6.0	5.2	4.6	6.9	5.8	5.1	4.5	6.5	5.6	5.0	4.4	6.1	5.4	4.8	4.4	4.1			
			1.25	7.7	6.7	5.9	5.3	7.5	6.5	5.8	5.3	7.1	6.3	5.7	5.2	6.7	6.0	5.5	5.1	4.7			
下方投影面積		cm <sup>2</sup>	1.5	8.1	7.2	6.5	5.9	7.9	7.0	6.4	5.8	7.5	6.8	6.2	5.7	7.1	6.5	6.0	5.6	5.2			
等価発光面積		cm <sup>2</sup>	2.0	8.7	7.9	7.3	6.8	8.5	7.8	7.2	6.7	8.0	7.4	6.9	6.5	7.6	7.1	6.7	6.4	6.0			
取付高さ	器具間隔最大限		2.5	9.1	8.4	7.8	7.4	8.8	8.2	7.7	7.3	8.4	7.9	7.5	7.1	8.0	7.6	7.2	6.9	6.5			
	横方向 (A)	縦方向 (B)	3.0	9.3	8.7	8.2	7.8	9.1	8.6	8.1	7.7	8.7	8.2	7.8	7.5	8.3	7.9	7.6	7.3	6.9			
Hm	1.37Hm	1.37Hm	4.0	9.6	9.2	8.8	8.4	9.4	9.0	8.6	8.3	9.0	8.6	8.3	8.0	8.6	8.3	8.0	7.8	7.4			
			5.0	9.8	9.4	9.1	8.8	9.6	9.3	8.9	8.6	9.2	8.9	8.6	8.4	8.8	8.6	8.4	8.1	7.7			
			7.0	10.1	9.8	9.5	9.3	9.9	9.6	9.3	9.1	9.5	9.2	9.0	8.8	9.1	8.9	8.7	8.6	8.1			
			10.0	10.2	10.0	9.8	9.6	10.0	9.8	9.7	9.5	9.6	9.5	9.3	9.2	9.3	9.1	9.0	8.9	8.4			

