

屋内照明器具特性	
品番 (品名)	LGC68200
光源	LED9999_70_6099 x1 6099.0lm
管理番号	K0155362(0)D1
BZ分類	BZ6/0.7/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 25%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	75%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良	0.63	0.6	51	39	31	26	49	37	30	25	44	34	28	24	39	32	26	22	19
	中	0.6	0.8	60	49	41	35	57	47	39	34	52	43	37	32	47	39	34	30	25
	否	0.56	1.0	67	56	48	42	63	53	46	40	57	49	43	38	51	45	40	35	30
			1.25	73	62	55	49	69	60	53	47	62	55	49	44	56	50	45	41	35
下方投影面積	cm ²		1.5	77	67	60	54	73	64	58	52	66	59	54	49	60	54	49	46	39
等価発光面積	cm ²		2.0	82	74	68	62	78	71	65	60	71	65	60	56	64	60	56	52	45
取付高さ	器具間隔最大限		2.5	86	79	73	68	82	76	70	66	74	69	65	61	68	64	60	57	49
	横方向 (A)	縦方向 (B)	3.0	88	82	77	72	84	79	74	70	77	72	69	65	70	66	63	60	53
1.5m	1.95m	2.01m	4.0	92	87	82	78	88	83	79	76	80	77	73	70	73	70	68	65	57
2	2.57	2.65	5.0	94	90	86	82	90	86	83	79	82	79	76	74	75	73	70	68	60
2.5	3.21	3.3	7.0	96	93	90	87	92	89	87	84	85	82	80	78	77	76	74	72	63
3	3.82	3.92	10.0	98	96	93	91	94	92	90	88	87	85	83	82	79	78	77	75	66

