

屋内照明器具特性	
品番 (品名)	NNF 2 2 9 1 0 J
光源	LDL20S.N/11/12-K(960) ×2 960.0 l m
管理番号	K0125037(0)DR1
BZ分類	BZ5

器具効率	95 %	天井	80 %				70 %				50 %				30 %				0 %			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %			
下方光束	95 %	室指数	照明率 (X0.01) ZCM																			
保守率	良 0.81 中 0.77 否 0.68	0.6	53	41	33	28	52	40	33	28	49	39	33	28	47	38	32	28	26			
		0.8	62	51	44	38	61	51	43	38	58	49	43	38	56	48	42	38	36			
		1.0	69	58	51	45	67	58	51	45	64	56	50	45	62	55	49	45	42			
		1.25	75	65	58	53	73	64	58	53	70	63	57	52	67	61	56	52	49			
下方投影面積	c m ²	1.5	79	70	64	58	77	69	63	58	74	67	62	57	71	66	61	57	55			
		2.0	84	77	71	67	83	76	71	66	80	74	70	66	77	72	68	65	62			
取付高さ	器具間隔最大限		2.5	88	82	77	72	86	81	76	72	83	79	75	71	81	77	73	70	68		
	横方向 (A)	縦方向 (B)	3.0	90	85	80	77	89	84	80	76	86	82	78	75	83	80	77	74	72		
1.5m	2.07 m	1.91 m	4.0	93	89	86	82	92	88	85	82	89	86	83	80	87	84	81	79	77		
2	2.75	2.51	5.0	95	92	89	86	94	91	88	85	91	88	86	84	89	86	84	82	80		
2.5	3.44	3.12	7.0	97	95	92	90	96	94	91	89	93	91	90	88	91	89	88	86	84		
3	4.14	3.73	10.0	99	97	95	94	98	96	94	93	95	94	92	91	93	92	91	90	87		

