

# 屋内照明器具特性

品番 (品名)	LGBZ6113	
光源	LED6200_70_3650 x1	3650.0 lm
管理番号	K0164174(0)D 1	
BZ分類	BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 21%		下方光束 79%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
室指数	照明率 ( X0.01 )																				ZCM
保守率	良	0.63	0.6	56	44	37	32	53	43	36	31	49	40	34	30	45	38	33	29	26	
	中	0.6	0.8	65	55	48	42	63	53	46	41	58	50	44	40	53	47	42	38	34	
	否	0.56	1.0	72	62	55	50	69	60	53	49	63	56	51	46	58	52	48	44	40	
			1.25	78	69	62	57	74	66	60	56	69	62	57	53	63	58	54	50	45	
下方投影面積	cm <sup>2</sup>		1.5	81	73	67	62	78	71	65	61	72	66	62	58	67	62	58	55	49	
等価発光面積	cm <sup>2</sup>		2.0	87	80	75	70	83	77	72	68	77	72	68	65	71	67	64	61	55	
取付高さ	器具間隔最大限		2.5	90	84	80	75	87	81	77	73	80	76	73	69	74	71	68	66	59	
	横方向 (A)	縦方向 (B)	3.0	92	87	83	79	89	84	81	77	82	79	76	73	76	73	71	69	62	
Hm	1.21Hm	1.22Hm	4.0	95	91	88	85	92	88	85	82	85	82	80	77	79	77	75	73	66	
			5.0	97	93	91	88	93	90	88	85	87	84	82	80	80	79	77	75	68	
			7.0	99	96	94	92	95	93	91	89	89	87	85	84	82	81	80	79	71	
			10.0	100	98	97	95	97	95	94	92	90	89	88	87	84	83	82	81	73	

