

屋内照明器具特性

品番 (品名)	LGBZ7216									
光源	LED6200_70_3850 x1 3850.0 lm									
管理番号	K0163277(1)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束		10%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		90%		床	10%				10%				10%				10%				0%	
室指数	照明率 (X0.01) ZCM																						
保守率	良	0.63	0.6	0.6	0.56	0.6	55	43	35	30	53	42	35	29	50	40	33	29	47	38	32	28	25
	中	0.6	0.6	0.6	0.6	0.8	64	53	45	39	62	52	44	39	58	49	43	38	55	47	41	37	34
	否	0.56	0.56	0.56	0.56	1.0	71	60	52	46	69	59	51	46	64	56	49	44	60	53	48	43	40
						1.25	77	67	59	53	74	65	58	53	70	62	56	51	66	59	54	50	46
下方投影面積			cm ²		1.5	81	71	64	59	78	70	63	58	73	66	61	56	69	63	58	54	50	
			cm ²		2.0	86	78	72	67	84	76	71	66	79	73	68	64	74	69	65	61	57	
取付高さ	器具間隔最大限				2.5	90	83	77	72	87	81	76	71	82	77	73	69	78	73	70	66	62	
	横方向 (A)		縦方向 (B)		3.0	92	86	81	77	90	84	79	75	85	80	76	73	80	76	73	70	65	
1.5m	1.84m	1.85m	1.85m	4.0	95	90	86	82	93	88	84	81	88	84	81	78	84	81	78	75	70		
2	2.41	2.44	2.44	5.0	97	93	90	86	95	91	88	85	90	87	84	82	86	83	81	79	74		
2.5	3.01	3.03	3.03	7.0	100	97	94	91	97	94	92	89	93	90	88	86	88	86	84	83	77		
3	3.61	3.64	3.64	10.0	102	99	97	95	99	97	95	93	95	93	91	90	90	89	88	86	81		

