

# 屋内照明器具特性

品番 (品名)	XND9998SVK		
光源	LED3500_80_16330 x1 16330.0 1m		
管理番号	K0155306(0)DB1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%		
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	100%	床		10%				10%				10%				10%				0%	
室指数	照明率 ( X0.01 )																				ZCM
保守率	良 0.76	0.6	79	71	67	64	78	71	67	63	76	70	66	63	75	70	66	63	62		
	中 0.72		0.8	86	80	75	72	85	79	75	72	84	78	75	72	82	78	74	70		
	否 0.64		1.0	91	85	81	78	90	85	81	78	88	83	80	77	86	82	79	77	76	
下方投影面積 等価発光面積	cm <sup>2</sup>	1.25	94	90	86	83	93	89	85	83	92	88	85	82	90	87	84	82	80		
		1.5	97	92	89	86	96	92	89	86	94	90	88	85	92	89	87	85	83		
取付高さ	器具間隔最大限		2.5	102	99	96	94	101	98	96	94	98	96	94	93	96	95	93	90		
	横方向 (A)	縦方向 (B)	3.0	103	100	98	96	102	99	97	96	100	98	96	94	98	96	95	91		
Hm	0.76Hm	0.76Hm	4.0	104	102	101	99	103	101	100	98	101	99	98	97	99	98	97	93		
			5.0	105	104	102	101	104	103	101	100	102	101	99	98	100	99	98	95		
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	96		
			10.0	107	106	105	104	106	105	104	103	103	103	102	101	101	100	100	97		

