

屋内照明器具特性	
品番 (品名)	XND2579WN
光源	LED5000_85_2515 ×1 2515.0lm
管理番号	K0176095 (0) DB1
BZ分類	BZ1

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 8 1	0 . 6	7 2	6 3	5 7	5 4	7 1	6 3	5 7	5 3	6 9	6 2	5 7	5 3	6 7	6 1	5 7	5 3	5 2	
			0 . 7 7	0 . 8	8 1	7 3	6 8	6 4	8 0	7 3	6 8	6 4	7 8	7 2	6 7	6 4	7 6	7 1	6 7	6 4	6 2	
			1 . 0	8 7	8 0	7 5	7 2	8 6	7 9	7 5	7 1	8 4	7 8	7 4	7 1	8 2	7 7	7 4	7 1	6 9		
			0 . 6 8	1 . 2 5	9 1	8 6	8 1	7 8	9 0	8 5	8 1	7 7	8 8	8 3	8 0	7 7	8 6	8 2	7 9	7 6	7 5	
下方投影面積		c m ²	1 . 5	9 4	8 9	8 5	8 2	9 3	8 8	8 5	8 2	9 1	8 7	8 4	8 1	8 9	8 5	8 3	8 0	7 9		
等価発光面積			c m ²	2 . 0	9 8	9 4	9 0	8 8	9 7	9 3	9 0	8 7	9 5	9 1	8 9	8 6	9 2	9 0	8 7	8 5	8 4	
取付 高さ	器具間隔最大限		2 . 5	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 2	9 0	8 9	8 7		
	横方向 (A) 縦方向 (B)		3 . 0	1 0 1	9 9	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 1	8 9		
H m	1 . 1 3 H m	1 . 1 3 H m	4 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 8	9 6	9 5	9 4	9 1		
			5 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 9	9 8	9 6	9 5	9 3		
			7 . 0	1 0 5	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5		
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 3	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	1 0 0	9 9	9 6		

