

|          |                              |
|----------|------------------------------|
| 屋内照明器具特性 |                              |
| 品番 (品名)  | LGCX51163                    |
| 光源       | LED6200_70_5499 x1 5499.0 lm |
| 管理番号     | K0140109(0)DB1               |
| BZ分類     | BZ6/0.7/BZ5                  |

|        |                 |         |             |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     |     |     |
|--------|-----------------|---------|-------------|------|------|-----|-----|------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%            | 天井      | 80%         |      |      |     | 70% |      |     |     | 50% |     |     |     | 30% |     |     |     | 0%  |     |
|        |                 | 壁       | 70          | 50   | 30   | 10  | 70  | 50   | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 0%  |     |
| 上方光束   | 7%              | 床       | 10%         |      |      |     | 10% |      |     |     | 10% |     |     |     | 10% |     |     |     | 0%  |     |
| 下方光束   | 93%             | 室指数     | 照明率 (X0.01) |      |      |     |     |      |     |     |     |     |     |     |     |     |     |     | ZCM |     |
| 保守率    | 良               | 0.63    | 0.6         | 5.4  | 4.1  | 3.3 | 2.7 | 5.2  | 4.0 | 3.3 | 2.7 | 4.9 | 3.9 | 3.2 | 2.7 | 4.6 | 3.7 | 3.1 | 2.6 | 2.4 |
|        | 中               | 0.6     | 0.8         | 6.4  | 5.2  | 4.3 | 3.7 | 6.2  | 5.0 | 4.3 | 3.7 | 5.8 | 4.8 | 4.1 | 3.6 | 5.5 | 4.6 | 4.0 | 3.6 | 3.3 |
|        | 否               | 0.56    | 1.0         | 7.0  | 5.9  | 5.1 | 4.5 | 6.8  | 5.8 | 5.0 | 4.4 | 6.4 | 5.5 | 4.8 | 4.3 | 6.0 | 5.3 | 4.7 | 4.2 | 3.9 |
|        |                 |         | 1.25        | 7.6  | 6.6  | 5.8 | 5.2 | 7.4  | 6.4 | 5.7 | 5.2 | 7.0 | 6.2 | 5.5 | 5.0 | 6.6 | 5.9 | 5.4 | 4.9 | 4.6 |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5         | 8.0  | 7.1  | 6.4 | 5.8 | 7.8  | 6.9 | 6.3 | 5.7 | 7.4 | 6.6 | 6.0 | 5.6 | 7.0 | 6.4 | 5.9 | 5.4 | 5.1 |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0         | 8.6  | 7.8  | 7.2 | 6.6 | 8.4  | 7.6 | 7.0 | 6.5 | 7.9 | 7.3 | 6.8 | 6.4 | 7.5 | 7.0 | 6.6 | 6.2 | 5.8 |
| 取付高さ   | 器具間隔最大限         |         | 2.5         | 9.0  | 8.3  | 7.7 | 7.2 | 8.7  | 8.1 | 7.6 | 7.1 | 8.3 | 7.8 | 7.3 | 6.9 | 7.9 | 7.4 | 7.1 | 6.7 | 6.3 |
|        | 横方向 (A)         | 縦方向 (B) | 3.0         | 9.2  | 8.6  | 8.1 | 7.6 | 9.0  | 8.4 | 8.0 | 7.5 | 8.6 | 8.1 | 7.7 | 7.3 | 8.2 | 7.8 | 7.4 | 7.1 | 6.7 |
| Hm     | 1.36Hm          | 1.36Hm  | 4.0         | 9.6  | 9.1  | 8.6 | 8.2 | 9.3  | 8.9 | 8.5 | 8.1 | 8.9 | 8.5 | 8.2 | 7.9 | 8.5 | 8.2 | 7.9 | 7.6 | 7.2 |
|        |                 |         | 5.0         | 9.8  | 9.4  | 9.0 | 8.6 | 9.5  | 9.2 | 8.8 | 8.5 | 9.1 | 8.8 | 8.5 | 8.2 | 8.7 | 8.5 | 8.2 | 8.0 | 7.5 |
|        |                 |         | 7.0         | 10.0 | 9.7  | 9.4 | 9.1 | 9.8  | 9.5 | 9.2 | 9.0 | 9.4 | 9.1 | 8.9 | 8.7 | 9.0 | 8.8 | 8.6 | 8.4 | 7.9 |
|        |                 |         | 10.0        | 10.2 | 10.0 | 9.7 | 9.5 | 10.0 | 9.8 | 9.6 | 9.4 | 9.6 | 9.4 | 9.2 | 9.1 | 9.2 | 9.0 | 8.9 | 8.8 | 8.3 |

