

# 屋内照明器具特性

|         |                  |         |
|---------|------------------|---------|
| 品番 (品名) | LGD1002L         |         |
| 光源      | LED2700_70_50 x1 | 50.0 lm |
| 管理番号    | K0169239(0)DB1   |         |
| BZ分類    | BZ2              |         |

|        |         |                 |               |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |    |    |  |     |
|--------|---------|-----------------|---------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|----|--|-----|
| 器具効率   | 100%    | 天井              | 80%           |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |    |    | 0% |    |    |  |     |
|        | 上方光束    |                 | 0%            | 反射率 | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70 | 50 | 30 | 10 | 0% |  |     |
| 下方光束   | 100%    | 床               | 10%           |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |    |    | 0% |    |    |  |     |
| 室指数    |         |                 | 照明率 ( X0.01 ) |     |     |     |     |     |     |     |     |     |     |     |     |     |    |    |    |    |    |  | ZCM |
| 保守率    | 良       | 0.67            | 0.6           | 69  | 60  | 54  | 49  | 68  | 59  | 53  | 49  | 66  | 58  | 53  | 49  | 64  | 57 | 53 | 49 | 47 |    |  |     |
|        | 中       | 0.63            | 0.8           | 78  | 70  | 64  | 60  | 77  | 69  | 64  | 60  | 75  | 68  | 63  | 59  | 73  | 67 | 62 | 59 | 57 |    |  |     |
|        | 否       | 0.56            | 1.0           | 84  | 76  | 71  | 67  | 83  | 76  | 71  | 67  | 81  | 75  | 70  | 66  | 79  | 73 | 69 | 66 | 64 |    |  |     |
|        |         |                 | 1.25          | 89  | 82  | 78  | 74  | 88  | 82  | 77  | 73  | 86  | 80  | 76  | 73  | 83  | 79 | 75 | 72 | 71 |    |  |     |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5           | 92  | 86  | 82  | 78  | 91  | 86  | 81  | 78  | 89  | 84  | 80  | 77  | 87  | 83 | 79 | 77 | 75 |    |  |     |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0           | 97  | 92  | 88  | 85  | 95  | 91  | 87  | 84  | 93  | 89  | 86  | 83  | 91  | 88 | 85 | 83 | 81 |    |  |     |
| 取付高さ   | 器具間隔最大限 |                 | 2.5           | 99  | 95  | 92  | 89  | 98  | 94  | 91  | 88  | 95  | 92  | 90  | 87  | 93  | 91 | 88 | 86 | 84 |    |  |     |
|        | 横方向 (A) | 縦方向 (B)         | 3.0           | 101 | 97  | 94  | 92  | 99  | 96  | 93  | 91  | 97  | 94  | 92  | 90  | 95  | 93 | 91 | 89 | 87 |    |  |     |
| Hm     | 1.02Hm  | 1.02Hm          | 4.0           | 103 | 100 | 98  | 96  | 101 | 99  | 97  | 95  | 99  | 97  | 95  | 93  | 97  | 95 | 94 | 92 | 90 |    |  |     |
|        |         |                 | 5.0           | 104 | 102 | 100 | 98  | 103 | 101 | 99  | 97  | 100 | 99  | 97  | 96  | 98  | 97 | 95 | 94 | 92 |    |  |     |
|        |         |                 | 7.0           | 105 | 104 | 102 | 101 | 104 | 102 | 101 | 100 | 102 | 100 | 99  | 98  | 99  | 98 | 97 | 97 | 94 |    |  |     |
|        |         |                 | 10.0          | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 100 | 99 | 98 | 98 | 96 |    |  |     |

