

屋内照明器具特性

品番 (品名)	LGC61124														
光源	LED6200_70_5800 x1 5800.0 lm														
管理番号	K0168479(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	2%	室指数	照明率 (X0.01)																ZCM		
下方光束	98%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	5.5	4.2	3.4	2.9	5.3	4.2	3.4	2.9	5.1	4.0	3.3	2.8	4.8	3.9	3.3	2.8	2.6		
		0.8	6.5	5.3	4.5	3.9	6.3	5.2	4.5	3.9	6.0	5.1	4.4	3.9	5.8	4.9	4.3	3.8	3.6		
		1.0	7.2	6.1	5.3	4.7	7.0	6.0	5.2	4.6	6.7	5.8	5.1	4.6	6.4	5.6	5.0	4.5	4.3		
		1.25	7.8	6.8	6.0	5.4	7.6	6.7	6.0	5.4	7.3	6.5	5.8	5.3	7.0	6.3	5.7	5.3	5.0		
下方投影面積	c m ²	1.5	8.2	7.3	6.6	6.0	8.0	7.2	6.5	6.0	7.7	7.0	6.4	5.9	7.4	6.7	6.2	5.8	5.5		
		2.0	8.8	8.0	7.4	6.9	8.6	7.9	7.3	6.8	8.3	7.7	7.2	6.7	7.9	7.4	7.0	6.6	6.3		
取付高さ	器具間隔最大限		2.5	9.2	8.5	7.9	7.5	9.0	8.4	7.8	7.4	8.6	8.1	7.7	7.3	8.3	7.9	7.5	7.2	6.9	
	横方向 (A)	縦方向 (B)	3.0	9.4	8.8	8.3	7.9	9.2	8.7	8.2	7.8	8.9	8.5	8.1	7.7	8.6	8.2	7.9	7.6	7.3	
H m	1.37 H m	1.37 H m	4.0	9.7	9.3	8.9	8.5	9.6	9.1	8.8	8.4	9.2	8.9	8.6	8.3	8.9	8.6	8.4	8.1	7.8	
			5.0	9.9	9.6	9.2	8.9	9.8	9.4	9.1	8.8	9.5	9.2	8.9	8.6	9.2	8.9	8.7	8.5	8.1	
			7.0	10.2	9.9	9.6	9.4	10.0	9.7	9.5	9.3	9.7	9.5	9.3	9.1	9.4	9.2	9.1	8.9	8.6	
			10.0	10.3	10.1	9.9	9.8	10.2	10.0	9.8	9.6	9.9	9.7	9.6	9.4	9.6	9.5	9.4	9.2	8.9	

