

屋内照明器具特性	
品番 (品名)	XND1536WY
光源	LED2700_85_1435 x1 1435.0lm
管理番号	K0176630(0)DB1
BZ分類	BZ1

器具効率		101 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																			ZCM	
下方光束		101 %																						
保守率		良 中 否	0.6	88	82	79	77	87	82	79	77	86	81	79	76	85	81	78	76	75				
			0.77	93	88	85	83	92	88	85	83	91	87	85	83	90	87	84	82	81				
			1.0	96	92	89	87	96	92	89	87	94	91	88	87	93	90	88	86	85				
			0.68	1.25	99	95	93	91	98	95	92	90	97	94	92	90	95	93	91	89	88			
下方投影面積 等価発光面積		cm ²	1.5	101	98	95	93	100	97	95	93	98	96	94	92	97	94	93	91	90				
			2.0	103	100	98	96	102	99	98	96	100	98	96	95	98	97	95	94	92				
取付 高さ	器具間隔最大限		2.5	104	102	100	98	103	101	99	98	101	100	98	97	99	98	97	96	94				
	横方向 (A)	縦方向 (B)	3.0	105	103	101	100	104	102	101	99	102	101	99	98	100	99	98	97	95				
H _m	0.76 H _m	0.76 H _m	4.0	106	104	103	102	105	104	103	102	103	102	101	100	101	100	99	98	96				
			5.0	107	105	104	103	105	104	103	102	103	103	102	101	101	101	100	99	97				
			7.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	101	98				
			10.0	108	107	107	106	107	106	106	105	104	104	104	103	102	102	102	101	99				

