

屋内照明器具特性

品番 (品名)	L G W 8 0 3 8 0									
光源	LED5000_70_565 ×1					565.0 l m				
管理番号	K0171392 (0) DB 1									
B Z 分類	B Z 9 / 0 . 9 / B Z 8									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	51 %	室指数																	照明率 (X 0 . 0 1)																	Z C M																
下方光束	49 %																																																			
保守率	良 中 否	0.63	0.6	0.56																																																
		0.6	0.6	0.56	0.6	45	32	24	19	41	29	22	17	33	24	19	14	26	20	15	11	6																														
		0.6	0.6	0.56	0.8	53	41	32	26	48	37	30	24	40	31	25	20	32	25	20	17	10																														
		0.56	0.6	0.56	1.0	59	47	39	32	54	43	36	30	44	36	30	25	35	29	24	21	13																														
下方投影面積	c m ²	1.25																																																		
		1.5	64	54	45	39	59	49	42	36	48	41	35	30	39	33	29	25	16																																	
等価発光面積	c m ²	2.0																																																		
		2.5	78	70	63	58	72	65	59	54	60	54	50	45	48	44	41	38	25																																	
取付高さ	器具間隔最大限																																																			
	横方向 (A)	縦方向 (B)																																																		
H m	1.62 H m	1.86 H m	3.0																																																	
			4.0	80	73	67	62	74	68	62	58	62	57	53	49	51	47	44	41	27																																
			5.0																																																	
			7.0																																																	
			10.0																																																	

