

# 屋内照明器具特性

品番 (品名) **LGB79212**

光源 LED2700\_70\_660 ×1 660.0 lm

管理番号 K0159029(0)DB1

BZ分類 BZ1

器具効率	101%	天井	80%				70%				50%				30%				0%			
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10				
上方光束	0%	反射率	10%				10%				10%				10%				0%			
下方光束	101%		室指数				照明率 (X0.01)															
保守率	良 0.67	0.6	77	70	65	62	77	69	65	62	75	69	64	61	74	68	64	61	60			
	中 0.63	0.8	85	78	73	70	84	77	73	69	82	76	72	69	80	75	72	69	67			
	否 0.56	1.0	89	83	78	75	88	82	78	75	86	81	77	74	84	80	77	74	73			
下方投影面積	cm <sup>2</sup>	1.25	93	87	83	80	92	87	83	80	90	85	82	79	88	84	81	79	77			
		1.5	96	91	87	84	94	90	86	83	92	88	85	83	90	87	84	82	80			
等価発光面積	cm <sup>2</sup>	2.0	99	95	92	89	98	94	91	88	96	92	90	88	94	91	89	87	85			
		2.5	101	98	95	92	100	97	94	92	98	95	93	91	95	93	91	90	88			
取付高さ	器具間隔最大限		3.0	102	99	97	95	101	98	96	94	99	97	95	93	97	95	93	92	90		
Hm	横方向 (A)	縦方向 (B)	4.0	104	102	100	98	103	101	99	97	101	99	97	96	98	97	96	94	92		
	0.43Hm	0.43Hm	5.0	105	103	101	100	104	102	101	99	102	100	99	98	99	98	97	96	94		
			7.0	106	105	103	102	105	104	103	101	103	102	101	100	101	100	99	98	96		
			10.0	107	106	105	104	106	105	104	103	104	103	102	101	101	101	100	100	97		

