

屋内照明器具特性

品番 (品名)	LGW40115	
光源	LDR11L-W/HB15 ×1	1000.0 1m
管理番号	K0167803(0)DR1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束 0%		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
下方光束	100%	床		10%				10%				10%				10%				0%			
室指数	照明率 (X0.01)																			ZCM			
保守率	良 0.67	0.6	0.6	87	82	78	76	86	81	78	76	85	81	78	76	84	80	78	76	75			
	中 0.63		0.8	92	88	85	82	92	87	84	82	90	87	84	82	89	86	83	82	81			
	否 0.56		1.0	96	92	89	86	95	91	88	86	93	90	88	86	92	89	87	85	84			
下方投影面積	cm ²	等価発光面積	cm ²	1.25	98	95	92	90	97	94	92	90	96	93	91	89	94	92	90	89	87		
				1.5	100	97	94	92	99	96	94	92	97	95	93	91	96	94	92	91	89		
取付高さ	器具間隔最大限		Hm	0.53Hm	0.53Hm	2.5	103	101	99	98	102	100	99	97	100	99	97	96	99	97	96	95	93
	横方向 (A)	縦方向 (B)				3.0	104	102	101	99	103	101	100	99	101	100	99	97	99	98	97	96	94
Hm	0.53Hm	0.53Hm	4.0	105	104	102	101	104	103	102	101	102	101	100	99	100	99	99	98	96			
			5.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96			
Hm	0.53Hm	0.53Hm	7.0	107	106	105	104	105	105	104	103	103	103	102	101	101	100	100	97				
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	101	98			

