

屋内照明器具特性

品番 (品名)	L G W C 8 5 2 2 5 B	
光源	LDC5L-E17/C/D/W/2 x1	360.0 l m
管理番号	K0169009(0)DR1	
BZ分類	BZ10	

器具効率	59%	天井	80%				70%				50%				30%				0%	
	上方光束		54%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	5%	床	10%				10%				10%				10%				0%	
室指数			照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	25	19	15	12	22	16	13	10	15	12	9	7	9	7	6	4	0
	中	0.6	0.8	30	24	19	16	26	20	17	14	18	14	12	10	11	9	7	6	0
	否	0.56	1.0	33	27	23	20	28	24	20	17	20	17	14	12	12	10	9	8	0
下方投影面積	等価発光面積	cm ²	1.25	36	31	27	23	31	27	23	20	22	19	16	15	13	11	10	9	0
			1.5	38	33	29	26	33	29	26	23	23	20	18	16	14	13	11	10	1
取付高さ	器具間隔最大限		2.0	41	37	33	30	36	32	29	27	25	23	21	19	15	14	13	12	1
	横方向 (A)	縦方向 (B)	2.5	43	39	36	33	37	34	32	29	26	24	23	21	16	15	14	13	1
H m	0.00H m	0.00H m	3.0	44	41	38	36	38	36	33	31	27	25	24	22	17	16	15	14	1
			4.0	46	43	41	39	40	38	36	34	29	27	26	24	18	17	16	15	2
			5.0	47	45	43	41	41	39	37	36	29	28	27	26	18	17	17	16	2
			7.0	48	47	45	43	42	41	39	38	30	29	28	27	19	18	18	17	2
			10.0	49	48	47	46	43	42	41	40	31	30	30	29	20	19	19	18	3

