

屋内照明器具特性

品番 (品名)	LGWC56020BF																	
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 1 m																	
管理番号	K0125232(1)DB1																	
BZ分類	BZ5																	

器具効率	42%	天井	80%				70%				50%				30%				0%				
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%			
上方光束	6%	反射率	10%				10%				10%				10%				0%				
下方光束	36%		床	10%				10%				10%				10%				0%			
室指数	照明率 (X0.01) ZCM																						
保守率	良 0.63 中 0.6 否 0.56	0.6	2.2	1.7	1.4	1.2	2.1	1.7	1.4	1.1	2.0	1.6	1.3	1.1	1.8	1.5	1.2	1.1	1.9				
		0.8	2.6	2.1	1.8	1.6	2.5	2.1	1.8	1.5	2.3	2.0	1.7	1.5	2.2	1.8	1.6	1.4	1.3				
		1.0	2.9	2.4	2.1	1.9	2.8	2.4	2.1	1.8	2.6	2.2	2.0	1.7	2.4	2.1	1.9	1.7	1.5				
		1.25	3.1	2.7	2.4	2.2	3.0	2.6	2.3	2.1	2.8	2.5	2.2	2.0	2.6	2.3	2.1	1.9	1.8				
下方投影面積	c m ²	1.5	3.3	2.9	2.6	2.4	3.2	2.8	2.6	2.3	3.0	2.7	2.4	2.2	2.7	2.5	2.3	2.1	1.9				
		2.0	3.6	3.2	3.0	2.7	3.4	3.1	2.9	2.7	3.2	2.9	2.7	2.5	3.0	2.8	2.6	2.4	2.2				
		2.5	3.7	3.4	3.2	3.0	3.6	3.3	3.1	2.9	3.3	3.1	2.9	2.8	3.1	2.9	2.8	2.6	2.4				
取付高さ	器具間隔最大限		H m	1.27 H m	1.27 H m	3.0	3.8	3.6	3.3	3.1	3.7	3.4	3.2	3.1	3.4	3.2	3.1	2.9	3.2	3.0	2.9	2.8	2.5
	4.0	3.9				3.7	3.6	3.4	3.8	3.6	3.5	3.3	3.6	3.4	3.3	3.2	3.3	3.2	3.3	3.2	3.1	3.0	2.7
			5.0	4.0	3.9	3.7	3.6	3.9	3.7	3.6	3.5	3.7	3.5	3.4	3.3	3.4	3.3	3.4	3.3	3.2	3.1	2.9	
			7.0	4.1	4.0	3.9	3.8	4.0	3.9	3.8	3.7	3.8	3.7	3.6	3.5	3.5	3.4	3.5	3.4	3.4	3.4	3.3	3.0
			10.0	4.2	4.1	4.0	3.9	4.1	4.0	3.9	3.8	3.8	3.8	3.7	3.6	3.6	3.6	3.6	3.6	3.5	3.4	3.1	

