

屋内照明器具特性

品番 (品名)	XND1000 WV	
光源	LED3500_85_935 ×1	935.0 lm
管理番号	K0158867 (0) DB 1	
BZ分類	BZ1/4.5 / BZ2/6.0 / BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %		壁	10 %				10 %				10 %				10 %				0 %
		床	10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.81	0.6	73	65	59	56	72	64	59	56	71	64	59	55	69	63	58	55	54	
	中 0.77	0.8	82	74	69	65	81	74	69	65	79	73	68	65	77	72	68	65	63	
	否 0.68	1.0	87	80	75	72	86	79	75	71	84	78	74	71	82	77	74	71	69	
下方投影面積	cm ²	1.25	91	85	81	77	90	85	80	77	88	83	79	76	86	82	79	76	74	
		1.5	94	89	85	81	93	88	84	81	91	87	83	80	89	85	82	80	78	
等価発光面積	cm ²	2.0	98	93	90	87	97	93	89	87	94	91	88	86	92	89	87	85	83	
		2.5	100	96	93	91	99	95	93	90	96	94	91	89	94	92	90	88	86	
取付高さ	器具間隔最大限		3.0	101	98	96	93	100	97	95	93	98	95	93	91	96	94	92	90	88
	横方向 (A)	縦方向 (B)	4.0	103	101	99	97	102	100	98	96	100	98	96	95	98	96	95	93	91
Hm	0.74 Hm	0.74 Hm	5.0	104	102	100	99	103	101	100	98	101	99	98	97	99	97	96	95	93
			7.0	105	104	103	101	104	103	102	100	102	101	100	99	100	99	98	97	95
			10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	99	99	96	96

