

屋内照明器具特性	
品番 (品名)	L G W C 8 5 2 1 0 Z
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0 l m
管理番号	K0140574(0)DB1
BZ分類	BZ10

器具効率	87%	天井	80%				70%				50%				30%				0%			
	上方光束		76%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
	下方光束		11%		床	10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM		
保守率	良中否	0.63	0.6	0.56	0.6	37	27	21	17	32	24	19	15	23	17	13	11	14	11	8	6	0
		0.6	0.8	44	34	28	23	38	30	24	20	27	21	17	14	17	13	11	9	0		
		1.0	1.0	49	39	33	28	42	34	29	25	30	24	21	18	18	15	13	11	0		
		0.56	1.25	53	44	38	33	46	39	33	29	32	28	24	21	20	17	15	13	1		
下方投影面積	等価発光面積	c m ²		1.5	56	48	42	37	49	42	37	33	35	30	27	24	22	19	17	15	1	
		c m ²		2.0	61	54	48	44	53	47	42	38	38	34	30	28	24	21	19	17	2	
取付高さ	器具間隔最大限		H m		2.5	63	57	53	48	55	50	46	42	40	36	33	31	25	23	21	19	2
	横方向 (A)	縦方向 (B)	0.00 H m	0.00 H m	3.0	65	60	56	52	57	53	49	45	41	38	35	33	26	24	22	21	3
			H m		4.0	68	64	60	56	59	56	52	50	43	40	38	36	27	26	24	23	4
			H m		5.0	70	66	63	60	61	58	55	52	44	42	40	38	28	27	26	24	4
			H m		7.0	72	69	66	64	63	60	58	56	46	44	42	41	30	29	27	26	5
			H m		10.0	73	71	69	67	64	63	61	59	47	46	45	43	31	30	29	28	6

