

屋内照明器具特性

品番 (品名)	XND0601WW															
光源	LED4000_85_570 x1 570.0 lm															
管理番号	K0158700(0)DB1															
BZ分類	BZ2/1.1/BZ1/1.4/BZ2/8.5/BZ1															

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	反射率	床	10%				10%				10%				10%				0%
下方光束	100%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否	0.81	0.6	70	61	55	51	69	61	55	51	67	60	55	51	66	59	54	51	49
		0.77	0.8	80	72	66	62	79	71	66	62	77	70	65	62	75	69	65	61	60
		0.68	1.0	86	78	73	69	84	78	73	69	82	77	72	69	80	75	71	68	67
			1.25	90	84	79	76	89	83	79	75	87	82	78	75	85	81	77	74	73
下方投影面積	c m ²	1.5	93	88	83	80	92	87	83	80	90	85	82	79	88	84	81	78	77	
		2.0	97	93	89	86	96	92	88	86	94	90	87	85	92	89	86	84	82	
取付高さ	器具間隔最大限		2.5	100	96	93	90	98	95	92	89	96	93	91	88	94	91	89	87	85
	横方向 (A)	縦方向 (B)	3.0	101	98	95	93	100	97	94	92	98	95	93	91	95	93	91	90	87
H m	1.16H m	1.16H m	4.0	103	100	98	96	102	99	97	95	99	97	96	94	97	96	94	93	90
			5.0	104	102	100	98	103	101	99	98	101	99	98	96	98	97	96	95	92
			7.0	105	104	102	101	104	103	101	100	102	101	100	99	100	99	98	97	94
			10.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96

