

屋内照明器具特性	
品番 (品名)	P M L E L 0 9 6 5 0 N S
光源	LED5000_70_2550 ×1 2550.0 lm
管理番号	K0177199 (0) DY 1
B Z 分類	BZ2 / 0.9 / BZ3 / 6.0 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		5 %		床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		9 5 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 9	0 . 6	6 6	5 6	5 0	4 5	6 5	5 5	4 9	4 5	6 2	5 4	4 9	4 5	6 0	5 3	4 8	4 4	4 2
			0 . 6 7	0 . 8	7 4	6 5	5 9	5 4	7 3	6 4	5 9	5 4	7 0	6 3	5 8	5 4	6 8	6 1	5 7	5 3	5 1
			0 . 6 3	1 . 0	8 0	7 2	6 5	6 1	7 8	7 1	6 5	6 0	7 5	6 9	6 4	6 0	7 2	6 7	6 2	5 9	5 7
				1 . 2 5	8 5	7 7	7 1	6 7	8 3	7 6	7 1	6 6	8 0	7 4	6 9	6 5	7 7	7 2	6 8	6 4	6 2
下方投影面積		c m ²		1 . 5	8 8	8 1	7 6	7 1	8 6	8 0	7 5	7 1	8 3	7 8	7 3	7 0	8 0	7 5	7 2	6 8	6 6
			等価発光面積	c m ²	2 . 0	9 2	8 7	8 2	7 8	9 1	8 5	8 1	7 7	8 7	8 3	7 9	7 6	8 4	8 0	7 7	7 4
取付 高さ	器具間隔最大限		2 . 5	9 5	9 0	8 6	8 2	9 3	8 9	8 5	8 1	9 0	8 6	8 3	8 0	8 6	8 3	8 1	7 8	7 5	
	横方向 (A)	縦方向 (B)	3 . 0	9 7	9 3	8 9	8 5	9 5	9 1	8 8	8 5	9 2	8 8	8 5	8 3	8 8	8 6	8 3	8 1	7 7	
1 . 5 m	1 . 0 4 m	1 . 8 4 m	4 . 0	9 9	9 6	9 3	9 0	9 7	9 4	9 1	8 9	9 4	9 1	8 9	8 7	9 1	8 8	8 6	8 5	8 1	
2	1 . 3 8	2 . 3 6	5 . 0	1 0 1	9 8	9 5	9 3	9 9	9 6	9 4	9 2	9 5	9 3	9 1	8 9	9 2	9 0	8 9	8 7	8 3	
2 . 5	1 . 7 2	2 . 8 9	7 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 7	9 6	9 4	9 2	9 4	9 3	9 1	9 0	8 6	
3	2 . 0 6	3 . 4 4	1 0 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 2	1 0 1	9 9	9 8	9 9	9 7	9 6	9 5	9 5	9 4	9 3	9 2	8 8	

