

# 屋内照明器具特性

品番 (品名)	LGD1126V	
光源	LED3500_70_485 ×1	485.0 lm
管理番号	K0160344(0)D 1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%			
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10				
上方光束	0%	反射率	10%				10%				10%				10%				0%			
下方光束	100%		室指数				照明率 ( X0.01)															
保守率	良 0.67	0.6	85	79	75	73	84	79	75	72	83	78	75	72	82	77	74	72	71			
	中 0.63	0.8	90	85	81	78	89	84	81	78	88	83	80	78	86	83	80	78	77			
	否 0.56	1.0	93	88	85	82	92	88	85	82	91	87	84	82	89	86	83	81	80			
下方投影面積	cm <sup>2</sup>	1.25	96	92	89	86	95	91	88	86	93	90	87	85	92	89	87	85	83			
		1.5	98	94	91	89	97	94	91	89	95	92	90	88	94	91	89	87	86			
等価発光面積	cm <sup>2</sup>	2.0	101	97	95	93	100	97	94	92	98	95	93	91	96	94	92	91	89			
		2.5	102	99	97	95	101	99	97	95	99	97	95	94	97	96	94	93	91			
取付高さ	器具間隔最大限		3.0	103	101	99	97	102	100	98	97	100	98	97	95	98	97	95	94	92		
	横方向 (A)	縦方向 (B)	4.0	104	103	101	100	103	102	100	99	101	100	99	98	99	98	97	96	94		
Hm	0.37Hm	0.37Hm	5.0	105	104	102	101	104	103	102	100	102	101	100	99	100	99	98	97	95		
			7.0	106	105	104	103	105	104	103	102	103	102	101	100	101	100	99	99	96		
			10.0	107	106	105	105	106	105	104	104	103	103	102	102	101	101	100	100	97		

