

屋内照明器具特性	
品番 (品名)	YYY24560K
光源	LED3500_70_510 ×1 510.0 lm
管理番号	K0178713 (1) DR1
BZ分類	BZ5

器具効率		100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.69	0.6	54	41	33	28	52	40	33	27	49	38	32	27	46	37	31	26	24	
			0.67	0.8	63	51	43	37	61	50	43	37	57	48	41	36	54	46	40	35	32	
			0.63	1.0	70	59	51	44	68	57	50	44	63	54	48	43	59	52	46	42	38	
			0.63	1.25	76	65	58	52	73	64	57	51	69	61	55	50	65	58	53	48	45	
下方投影面積		cm ²	1.5	80	70	63	57	77	69	62	56	73	65	60	55	69	62	57	53	49		
			等価発光面積	cm ²	2.0	85	77	71	65	83	76	69	64	78	72	67	62	74	69	64	60	56
取付 高さ	器具間隔最大限			2.5	89	82	76	71	87	80	75	70	82	76	72	68	77	73	69	66	61	
	横方向 (A)		縦方向 (B)	3.0	92	85	80	75	89	83	79	74	84	80	75	72	80	76	73	69	65	
1.5m	1.98 m	1.97 m	4.0	95	90	85	81	92	88	84	80	88	84	80	77	83	80	77	75	70		
2	2.65	2.61	5.0	97	93	89	85	95	91	87	84	90	87	84	81	85	83	80	78	73		
2.5	3.3	3.26	7.0	99	96	93	90	97	94	91	89	92	90	88	85	88	86	84	82	77		
3	3.96	3.91	10.0	101	99	97	94	99	97	95	93	94	93	91	89	90	89	87	86	81		

