

屋内照明器具特性	
品番 (品名)	XAD3402
光源	LLD3000CU1 ×1 795.0 lm
管理番号	K0178772 (0) DR 1
BZ分類	BZ5

器具効率		89 %	反射率	天井	80 %					70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %					10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																	
保守率		良 中 否	0.67	0.6	51	40	33	28	50	40	33	28	48	39	33	28	46	38	32	28	26	
			0.63	0.8	60	50	43	38	59	49	43	38	56	48	42	38	54	47	41	37	35	
			0.56	1.0	66	57	50	45	65	56	49	44	62	54	49	44	60	53	48	44	42	
				1.25	71	63	56	51	70	62	56	51	67	60	55	51	65	59	54	50	48	
下方投影面積		cm ²		1.5	75	67	61	56	74	66	61	56	71	65	60	56	68	63	59	55	53	
			等価発光面積	cm ²	2.0	80	74	68	64	79	73	68	63	76	71	66	63	73	69	65	62	60
取付高さ	器具間隔最大限		2.5	83	78	73	69	82	77	72	69	79	75	71	68	77	73	70	67	65		
	横方向 (A) 縦方向 (B)			3.0	85	81	76	73	84	80	76	72	81	78	74	71	79	76	73	70	68	
H m	1.25 H m	1.25 H m	4.0	88	84	81	78	87	83	80	77	84	81	79	76	82	79	77	75	73		
			5.0	90	87	84	81	88	86	83	81	86	84	81	79	84	82	80	78	76		
			7.0	92	89	87	85	90	88	86	84	88	86	85	83	86	84	83	82	79		
			10.0	93	92	90	88	92	90	89	88	90	88	87	86	88	86	85	84	82		

