

| 屋内照明器具特性 |                        |
|----------|------------------------|
| 品番 (品名)  | XLGB1136               |
| 光源       | LLD2000CU1 ×1 566.0 lm |
| 管理番号     | K0179050 (0) DR1       |
| BZ分類     | BZ3/4.5/BZ4            |

| 器具効率     |                     | 80 %            | 反射率    | 天井              | 80 %              |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|---------------------|-----------------|--------|-----------------|-------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |                     |                 |        | 壁               | 70                | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |                     |                 |        | 床               | 10 %              |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |                     |                 |        | 室指数             | 照明率 ( X0.01 ) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |                     | 良<br>中<br>否     | 0.67   | 0.6             | 51                | 43 | 38 | 34 | 50   | 43 | 38 | 34 | 49   | 42 | 37 | 34 | 47   | 41 | 37 | 34 | 32  |
|          |                     |                 | 0.63   | 0.8             | 59                | 51 | 46 | 42 | 58   | 50 | 45 | 42 | 56   | 49 | 45 | 41 | 54   | 48 | 44 | 41 | 40  |
|          |                     |                 | 0.56   | 1.0             | 63                | 56 | 51 | 47 | 62   | 55 | 51 | 47 | 60   | 54 | 50 | 47 | 58   | 53 | 49 | 46 | 45  |
|          |                     |                 |        | 1.25            | 67                | 61 | 56 | 52 | 66   | 60 | 56 | 52 | 64   | 59 | 55 | 52 | 62   | 58 | 54 | 51 | 50  |
| 下方投影面積   |                     | cm <sup>2</sup> |        | 1.5             | 70                | 64 | 60 | 56 | 69   | 63 | 59 | 56 | 67   | 62 | 58 | 55 | 65   | 61 | 57 | 55 | 53  |
|          |                     |                 | 等価発光面積 | cm <sup>2</sup> | 2.0               | 74 | 69 | 65 | 62   | 73 | 68 | 64 | 61   | 70 | 67 | 63 | 61   | 68 | 65 | 62 | 60  |
| 取付<br>高さ | 器具間隔最大限             |                 |        | 2.5             | 76                | 72 | 68 | 65 | 75   | 71 | 68 | 65 | 73   | 69 | 67 | 64 | 71   | 68 | 66 | 63 | 62  |
|          | 横方向 ( A ) 縦方向 ( B ) |                 |        | 3.0             | 78                | 74 | 71 | 68 | 76   | 73 | 70 | 68 | 74   | 72 | 69 | 67 | 72   | 70 | 68 | 66 | 64  |
| H m      | 1.32 H m            | 1.32 H m        |        | 4.0             | 80                | 77 | 74 | 72 | 79   | 76 | 74 | 71 | 76   | 74 | 72 | 70 | 74   | 73 | 71 | 69 | 67  |
|          |                     |                 |        | 5.0             | 81                | 79 | 76 | 74 | 80   | 78 | 76 | 74 | 78   | 76 | 74 | 73 | 76   | 74 | 73 | 72 | 69  |
|          |                     |                 |        | 7.0             | 82                | 81 | 79 | 77 | 81   | 80 | 78 | 77 | 79   | 78 | 77 | 75 | 77   | 76 | 75 | 74 | 72  |
|          |                     |                 |        | 10.0            | 83                | 82 | 81 | 80 | 82   | 81 | 80 | 79 | 80   | 79 | 79 | 78 | 79   | 78 | 77 | 76 | 74  |

