

屋内照明器具特性	
品番 (品名)	XLGB1041
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0179040 (0) DR 1
BZ分類	BZ2 / 8.5 / BZ1

器具効率		62 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	41	35	31	28	40	35	31	28	39	34	31	28	38	34	30	28	27
			0.63	0.8	48	42	39	36	47	42	39	36	46	41	38	36	44	41	38	36	35
			0.56	1.0	52	47	44	41	51	47	43	41	50	46	43	41	48	45	43	41	40
				1.25	55	51	48	45	54	50	48	45	53	50	47	45	51	49	46	45	44
下方投影面積 等価発光面積		cm ²		1.5	57	53	51	48	56	53	50	48	55	52	50	48	53	51	49	47	46
				2.0	60	57	54	52	59	56	54	52	57	55	53	52	56	54	52	51	50
				2.5	61	59	57	55	60	58	56	55	59	57	55	54	57	56	55	53	52
				3.0	62	60	58	57	61	59	58	56	60	58	57	56	58	57	56	55	53
H _m	1.28H _m	1.28H _m		4.0	63	62	60	59	63	61	60	59	61	60	59	58	60	59	58	57	55
				5.0	64	63	62	60	63	62	61	60	62	61	60	59	60	60	59	58	57
				7.0	65	64	63	62	64	63	62	62	63	62	61	61	61	61	60	60	58
				10.0	65	65	64	63	65	64	63	63	63	63	62	62	62	61	61	61	59

